

Code: GTX-CLM1-10-8G2G

SWITCH POE **GTX-CLM1-10-8G2G** 8-PORT

Net: **124.09 GBP** Gross: **124.09 GBP**

Due to the reliability and ensuring high quality of transmission, the GTX-CLM1-10-8G2G 8-port PoE switch is an ideal solution for applications in CCTV IP installations. PoE powering possibility, compatible with the 802.3af/at standard makes the device more universal and easier to install.

Attention! When the Extend function is enabled the PoE range increases up to 250m and the transmission speed reduces to 10 Mb/s.



SPECIFICATION

LAN ports:	• 8 x RJ45 (2 x Hi-PoE + 6 x PoE (802.3af/at)), • 2 x RJ45 - Uplink
Management:	✓
Transmission speed:	10 / 100 / 1000 Mbps : 2 x Port LAN - Uplink + 8 x Port LAN & PoE
Operation modes:	• N - Normal - the device operates as normal PoE switch • V - VLAN (Port Isolation) - 1 ... 8 ports are isolated from each other and separately work with the 9, 10 ports • S - Extend - Range : 250 m @ 10 Mbps
Default IP address:	192.168.2.1
Default admin user / password:	admin / admin
Maximal output power:	• 90 W / port Hi-PoE - 1, 2 ports • 30 W / port PoE - 3 ... 8 ports
Maximal total power:	120 W
Main features:	• MDI/MDI-X auto detection feature - auto detecting the data transmission mode • Auto-learning and Auto-aging functions support for MAC addresses • QoS - mechanisms, which provide the high quality of transmission • MTBF (Mean Time Between Faults) : 50000 h
LED diodes:	PWR, PoE, Link/Act
Certificates:	CE, FCC, RoHS
Protections:	Overvoltage $\pm$ 4 kV
Power supply:	48 ... 57 V DC, Power adapter included
Housing:	Metal
Operation temp:	-10 °C ... 55 °C
Weight:	0.45 kg
Dimensions:	185 x 95 x 27 mm
Guarantee:	2 years

PRESENTATION



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Front view:



- 1 - LAN + PoE
 - 2 - LAN: Uplink
- Rear view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------