

Code: RG-ES110D-P

SWITCH POE **RG-ES110D-P** 8-PORT REYEE

Net: **90.93 EUR** Gross: **90.93 EUR**

Due to the reliability and ensuring high quality of transmission, the RG-ES110D-P 8-port PoE switch is an ideal solution for applications in CCTV IP installations. 8 ports support Power over Ethernet (PoE) function.



SPECIFICATION

LAN ports:	• 8 x RJ45 10/100 Base-T (8 x PoE (802.3af/at)), • 2 x RJ45 10/100/1000 Base-T - Uplink
Management:	—
Number of fan coolers:	—
LED diodes:	Power, PoE, Link/Act
Transmission speed:	• 10 / 100 Mbps : 8 LAN & PoE ports • 10 / 100 / 1000 Mbps : 2 Uplink ports
Maximal output power:	30 W / port PoE
Maximal total power:	110 W
Switching performance:	5.6 Gb/s
Packet redirection speed:	4.17 Mpps
MAC addresses table:	2k
Mobile phones support:	Android: Free application Ruijie Reyee iOS (iPhone): Free application Ruijie Reyee
Operation modes:	• Flow Control ON - Data flow control is enabled and all ports can communicate with each other, • Flow Control OFF - Data flow control is disabled and all ports can communicate with each other, • Port Isolation - 1 ... 8 ports are isolated from each other and separately work with the 9, 10 ports
Main features:	• View device status • protection against lightning discharges and voltage differences and strokes between devices • Grounding • MTBF (Mean Time Between Faults) > 200 000 h • IEEE 802.3az - 1 ... 8 ports • IEEE802.3x Flow Control
Certificates:	CE, RoHS
Protections:	Protection against lightning discharges : 6 kV
Housing:	Desktop, Metal

Power supply:	53.5 V DC / 2.24 A (power adapter included)
Power consumption:	≤ 129 W
Operation temp:	0 °C ... 45 °C
Weight:	0.52 kg
Dimensions:	191 x 105 x 28 mm
Manufacturer / Brand:	RUIJIE / REYEE
Guarantee:	3 years

PRESENTATION

Front panel:



Rear view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------