

Code: RS-UPS-98R

POE SWITCH WITH BATTERY BACKUP 9-PORT TO RACK CABINET **RS-UPS-98R PULSAR**

Net: **220.68 EUR** Gross: **220.68 EUR**

The RS-UPS-98R PoE Switch is a complete solution for power supply and battery backup of 8 IP cameras (48V DC power supply) and uninterruptible power supply of the DVR (12V DC power supply) in RACK 19" standard. In case of mains power loss, a battery back-up is activated immediately. Automatic detection of any devices powered in the PoE 802.3af standard is enabled at the 1 - 8 ports of the switch. The UP LINK port is used to connect another network device.



SPECIFICATION

LAN ports:	9 x RJ45 (8 x PoE (802.3af))
Port Uplink:	1 x RJ45
Transmission method:	Store and Forward
LED diodes:	Power AC, Power DC, TEMP, Low battery voltage, NVR, ALARM, Power Switch, PoE, Link/Act
Transmission speed:	10 / 100 Mbps - 9 x LAN & PoE ports
Maximal output power:	<ul style="list-style-type: none">• 15.4 W / port PoE,• 60 W - Power supply 12V DC
Maximal total power:	172 W
MAC addresses table:	1k - Auto update of MAC addresses table
Certificates:	CE
Power supply:	176 ... 264 V AC
Alarm inputs / outputs:	0 / 1 - ALARM technical output 1A @ 30VDC/50VAC type (NO/NC)
Housing:	Steel - powder painted
Color:	Black (RAL 9005)
Housing type:	RACK 19", 2U
Weight:	7.14 kg
Dimensions:	482 x 263 x 88 mm
Manufacturer / Brand:	PULSAR
Guarantee:	2 years

PRESENTATION

Front panel:

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



- 1. LAN + PoE
- 2. LAN + PoE
- 3. LAN + PoE
- 4. LAN + PoE
- 5. LAN + PoE
- 6. LAN + PoE
- 7. LAN + PoE
- 8. LAN + PoE
- 9. LAN

Rear panel:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------