

Code: BCS-B-SP1602G-2SFP(II)

SWITCH POE **BCS-B-SP1602G-2SFP(II)** 16-PORT SFP BCS BASIC

Net: **276.84 EUR** Gross: **276.84 EUR**

Due to the reliability and ensuring high quality of transmission, the BCS-B-SP1602G-2SFP(II) 16-port PoE switch is an ideal solution for applications in CCTV IP installations. PoE powering possibility, compatible with the 802.3af / 802.3at standard makes the device more universal and easier to install.



SPECIFICATION

LAN ports:	<ul style="list-style-type: none">• 2 x port Combo: SFP (Base-X) / RJ45 (Base-T)• 16 x RJ45 (16 x PoE (802.3at))
Management:	—
LED diodes:	Power, Act, PoE
Transmission speed:	<ul style="list-style-type: none">• 10 / 100 Mbps - 16 LAN & PoE ports,• 10 / 100 / 1000 Mbps - 2 Uplink ports,• 1000 Mbps - 2 SFP ports
Maximal output power:	30 W / port PoE
Maximal total power:	150 W
Main features:	<ul style="list-style-type: none">• 2 x Port Uplink• 4 operating modes: AI VLAN, AI EXTEND, AI PoE, AI QoS - selectable by switch• AI VLAN mode - ports 1 ... 16 are isolated from ports 17, 18• AI EXTEND mode - ports 1 ... 8 support transmission up to 250 m (cat5e, cat6)• AI QOS (Quality Of Service) mode - prioritization of video packets• AI PoE mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected
Certificates:	CE
Power supply:	100 ... 240 V AC
Weight:	2.26 kg
Dimensions:	440 x 180 x 44 mm
Manufacturer / Brand:	BCS BASIC
Guarantee:	2 years

PRESENTATION

Front view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

1. LAN + PoE

2. LAN

Rear view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60