

Code: TD-W8960N

ACCESS POINT +ROUTER **TD-W8960N** 300Mb/s ADSL

Net: **27.21 EUR** Gross: **27.21 EUR**

The TD-W8960N router has been designed for sharing Internet connection provided by ADSL Annex A technology. It has built-in ADSL modem compatible with ADSL/ADSL2/ADSL2+, Access Point works in IEEE802.11b/g/n standards enabling transmission speed up to 300Mb/s and 4-port switch. The WAN port assembled as RJ11 socket connects directly with telephone line.

The distinctive feature of the device is support for 802.11n standard - capability of using data transfer speeds up to 300Mb/s. The TD-W8960N ensures advanced access control and NAT, its DHCP server supports static assignment of IP addresses. The device also supports virtual servers, DMZ zone, remote logging and management.



SPECIFICATION

Frequency range:	2.4 ... 2.4835 GHz
Standards:	IEEE 802.11 b/g/n
LAN ports:	4x RJ-45 (10/100 Mbps, Auto MDI/MDX)
WAN interface:	1x RJ-11, ADSL/ADSL2/ADSL2+ Annex A
Transmitter power:	• 19 dBm IEEE 802.11n • 17 dBm IEEE 802.11b • 13.5 dBm IEEE 802.11g
Baud rates:	• 300 Mbps Wi-Fi • 100 Mbps LAN
Operation mode:	Access Point
ADSL standards:	Full-rate ANSI T1.413 Issue 2, ITU-T G.992.1(G.DMT), ITU-T G.992.2(G.Lite) ITU-T G.994.1 (G.hs), ITU-T G.995.1, ITU-T G.996.1, ITU-T G.997.1, ITU-T K.2.1
ADSL2 standards:	ITU-T G.992.3 (G.dmt.bis), ITU-T G.992.4 (G.lite.bis)
ADSL2+ standards:	ITU-T G.992.5
DHCP server:	✓
Firmware update:	✓
DDNS:	✓
Protections:	• LAN : Firewall, MAC addresses filtering, IP addresses filtering, parental control, LAN ACL • WLAN : WEP 64/128-bit, WPA-PSK/WPA2-PSK, TKIP/AES
Management interface:	Web browser

Operation temp:	0 °C ... 40 °C
Permissible relative humidity:	max. 90 %
Power supply:	12 V DC / 1 A (power adapter included)
Dimensions:	195 x 133 x 45 mm
Guarantee:	2 years

PRESENTATION

Front panel:



Rear panel:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------