

Code: BCS-CVR0801-III

HD-CVI, PAL, TCP/IP DVR **BCS-CVR0801-III** 8 CHANNELS

Net: **216.69 EUR** Gross: **216.69 EUR**

Tribrid DVR working in three standards: HD-CVI, IP and analog. The HD-CVI interface allows to transmission of analog, composite video signal via coaxial cable. Via single coaxial cable can be transmitted three signals: video, audio and control. It enables the transmission of HD resolution images for even 500 m distance with keeping the low costs of the installation. During transmission there are no delays and is maintained the original, high quality image.



SPECIFICATION

Standard:	HD-CVI, PAL, TCP/IP
Maximal total frame rate:	<ul style="list-style-type: none">• HD-CVI : max. 120 fps @ 1920 x 1080 px,• CVBS : max. 200 fps @ 960 x 576 px• IP : max. 100 fps @ 1920 x 1080 px
Recording speed adjustment:	<ul style="list-style-type: none">1 ... 25 fps @ 960 x 576 px1 ... 25 fps @ 1280 x 720 px1 ... 15 fps @ 1920 x 1080 px - HD-CVI1 ... 12 fps @ 1920 x 1080 px - IP for each channel
Supported resolutions:	<ul style="list-style-type: none">• 8 x HD-CVI @ 1080p or 8 x CVBS @ 960H• 7 x HD-CVI @ 1080p or 7 x CVBS @ 960H + 1 x IP @ 1080p• 6 x HD-CVI @ 1080p or 6 x CVBS @ 960H + 2 x IP @ 1080p
Video inputs:	8 pcs BNC - HD-CVI / Composite Video (CVBS)
Video outputs:	<ul style="list-style-type: none">1 pcs HDMI1 pcs VGA
Audio inputs:	1 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.264
Number of compression levels:	5
Image records resolutions:	<ul style="list-style-type: none">1920 x 10801280 x 720960 x 576704 x 576352 x 576704 x 288352 x 288176 x 144
Recording modes:	Manual, Motion Detection, Schedule
Supported hard drives:	1 x 6 TB SATA
External storage devices backup:	Save single frames and whole records from DVR drive to the USB drive
Searching and playback the records:	Records searching: by time + timeline with record type. Playback: forward, fast, slow, step Advanced searching (to the one second accuracy)

Network functions:	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters - PSS application Support : 3G, WiFi
Network protocols:	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP
Bitrate:	max. 32768 kbps (total)
Mobile phones support:	Android, iOS (Apple iPhone), BlackBerry, Windows Phone, Symbian - DMSS application
Alarm inputs / outputs:	—
PTZ control:	RS-485 PELCO-D/P
Motion Detection:	Split the screen into zones 22 x 18 motion zones Very good sensitivity, after motion detection records detected channels only
Mouse support:	✓
IR remote controller in the set:	—
Power supply:	12 V DC / 2 A (power adapter included)
Weight:	1.28 kg
Dimensions:	325 x 257 x 55 mm
Supported languages:	English, Polish
Country of origin:	China
Guarantee:	2 years
Manufacturer / Brand:	BCS

PRESENTATION

Front view:



Rear view:



In the kit:



OUR OPINIONS



- Bi-directional audio transfer via network.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

