

Code: BCS-CVR1602-II

## HD-CVI, PAL, TCP/IP DVR **BCS-CVR1602-II**

Net: **452.75 EUR** Gross: **452.75 EUR**

Tribrid DVR working in three standards: HD-CVI, IP and analog. The HD-CVI interface allows to transmission of analog, composite video signal via coaxial cable. Via single coaxial cable can be transmitted three signals: video, audio and control. It enables the transmission of HD resolution images for even 500 m distance with keeping the low costs of the installation. During transmission there are no delays and is maintained the original, high quality image.



### SPECIFICATION

Standard:	IP, HD-CVI, CVBS
Maximal total frame rate:	HD-CVI / IP : 200 fps @ 1920 x 1080 px, 400 fps @ 1280 x 720 px HD-CVI / Composite Video (CVBS) : 400 fps @ 960 x 576 px, 400 fps @ 704 x 576 px, 400 fps @ 352 x 576 px, 400 fps @ 704 x 288 px, 400 fps @ 352 x 288 px, 400 fps @ 176 x 144 px
Recording speed adjustment:	1 ... 12 fps @ 1920 x 1080 px 1 ... 25 fps @ 1280 x 720 px 1 ... 25 fps @ 960 x 576 px 1 ... 25 fps @ 704 x 576 px 1 ... 25 fps @ 352 x 576 px 1 ... 25 fps @ 704 x 288 px 1 ... 25 fps @ 352 x 288 px 1 ... 25 fps @ 176 x 144 px for each channel!
Supported resolutions:	14 pcs HD-CVI @ 1080p / 14 pcs Composite Video (CVBS) @ 960H + 2 pcs IP @ 1080p, 16 pcs HD-CVI @ 1080p / 16 pcs Composite Video (CVBS) @ 960H
Video inputs:	16 pcs BNC ( HD-CVI / Composite Video (CVBS) )
Video outputs:	1 pcs HDMI 1 pcs VGA
Audio inputs:	4 pcs CINCH - Bi-directional audio streaming support
Audio outputs:	1 pcs CINCH
Image compression method:	H.264
Number of compression levels:	5
Image records resolutions:	1920 x 1080 1280 x 720 960 x 576 704 x 576 352 x 576 704 x 288 352 x 288 174 x 144
Recording modes:	Manual, Sensor, Motion detection, Schedule

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

Supported hard drives:	2 x 4 TB SATA
External storage devices backup:	Download records from backup to USB drive
Searching and playback the records:	Records searching: by time + timeline with record type. Playback: forward, fast, slow, step Advanced searching (to the one second accuracy)
Network functions:	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters
Network protocols:	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP
Bitrate:	max. 160 Mbps (total)
Mobile phones support:	Available applications for mobile systems: iPhone, Android, Windows Mobile, Blackberry, Symbian
Alarm inputs / outputs:	16 pcs Input / 3 pcs Output
PTZ control:	RS-485, PELCO-D/P, Many protocols
Motion Detection:	Split the screen into zones 22 x 18 motion zones Very good sensitivity after motion detection records detected channels only
Mouse support:	✓
IR remote controller in the set:	✓
Power supply:	12 V DC / 5 A
Weight:	1.99 kg
Dimensions:	375 x 285 x 55 mm
Supported languages:	English, Chinese, Polish
Country of origin:	China
Guarantee:	2 years
Manufacturer / Brand:	BCS

## PRESENTATION

Front view:



Rear view:



In the kit:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60



## PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------