

																									
	25.16 EUR 25.16 EUR	28.65 EUR 28.65 EUR	27.48 EUR 27.48 EUR	26.71 EUR 26.71 EUR	25.16 EUR 25.16 EUR	42.58 EUR 42.58 EUR	52.50 EUR 52.50 EUR	45.97 EUR 45.97 EUR	61.69 EUR 61.69 EUR	75.73 EUR 75.73 EUR	58.06 EUR 58.06 EUR	75.00 EUR 75.00 EUR	53.23 EUR 53.23 EUR	57.82 EUR 57.82 EUR	72.10 EUR 72.10 EUR	75.73 EUR 75.73 EUR	87.58 EUR 87.58 EUR	104.52 EUR 104.52 EUR	53.23 EUR 53.23 EUR	49.60 EUR 49.60 EUR	93.63 EUR 93.63 EUR	78.15 EUR 78.15 EUR	65.32 EUR 65.32 EUR		
Standard	AHD, HD-CVI, HD-TVI	AHD, HD-CVI, HD-TVI	AHD, HD-CVI, HD-TVI	AHD, HD-CVI, HD-TVI	AHD, HD-CVI, HD-TVI	AHD, HD-CVI, HD-TVI, PAL	AHD, HD-CVI, HD-TVI, PAL	AHD, HD-CVI, HD-TVI, CVBS	AHD, HD-CVI, HD-TVI, CVBS	AHD, HD-CVI, HD-TVI, CVBS	AHD, HD-CVI, HD-TVI, PAL	AHD, HD-CVI, HD-TVI, CVBS	AHD, HD-CVI, HD-TVI, CVBS	AHD, HD-CVI, HD-TVI, CVBS	AHD, HD-CVI, HD-TVI, CVBS	AHD, HD-CVI, HD-TVI, CVBS	AHD, HD-CVI, HD-TVI, CVBS	AHD, HD-CVI, HD-TVI, CVBS	AHD / HD-CVI / HD-TVI / PAL	AHD / HD-CVI / HD-TVI / PAL	AHD / HD-CVI / HD-TVI / PAL	AHD / HD-CVI / HD-TVI / PAL	AHD / HD-CVI / HD-TVI / PAL	AHD / HD-CVI / HD-TVI / PAL	
Matrix size	5 Mpx	5 Mpx	5 Mpx	5 Mpx	5 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	2.1 Mpx	
Sensor	1/2.7 " Progressive Scan CMOS	1/3 " Progressive Scan CMOS	1/3 " Progressive Scan CMOS	1/2.7 " Progressive Scan CMOS	1/3 " Progressive Scan CMOS	1/2.7 " Progressive Scan CMOS	1/2.7 " Progressive Scan CMOS	Progressive Scan CMOS	Progressive Scan CMOS	Progressive Scan CMOS	Progressive Scan CMOS	Progressive Scan CMOS	Progressive Scan CMOS	Progressive Scan CMOS	1/2.7 " CMOS	1/2.7 " CMOS	Progressive Scan CMOS	1/2.8 " CMOS	Progressive Scan CMOS	Progressive Scan CMOS	Progressive Scan CMOS	Progressive Scan CMOS	Progressive Scan CMOS	Progressive Scan CMOS	
White light LED illuminator range	--	--	--	--	--	--	--	20 m	20 m	--	--	--	--	--	40 m	--	--	--	--	--	--	--	--	--	
Resolution	• 2592 x 1444 - 5 Mpx @ AHD / HD-TVI @ 20 fps / 12.5 fps. • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 25 fps. • 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 25 fps	• 2592 x 1444 - 5 Mpx @ AHD / HD-TVI @ 20 fps / 12.5 fps. • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 25, 30 fps. • 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 25, 30 fps	• 2592 x 1444 - 5 Mpx @ AHD / HD-TVI @ 20 fps / 12.5 fps. • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 25, 30 fps. • 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 25, 30 fps	• 2592 x 1444 - 5 Mpx @ AHD / HD-TVI @ 20 fps / 12.5 fps. • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 25, 30 fps. • 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 25, 30 fps	• 2592 x 1444 - 5 Mpx @ AHD / HD-TVI @ 20 fps / 12.5 fps. • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 25, 30 fps. • 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 25, 30 fps	• 2592 x 1444 - 5 Mpx @ AHD / HD-TVI @ 20 fps / 12.5 fps. • 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 25, 30 fps. • 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI @ 25, 30 fps	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H, PAL	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H, PAL	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H @ AHD / HD-CVI / HD-TVI @ 25 fps. • 960 x 576 - 960H @ PAL	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H @ AHD / HD-CVI / HD-TVI @ 25 fps. • 960 x 576 - 960H @ PAL	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H @ HD-CVI / HD-TVI / AHD @ 25 fps , 960 x 576 - 960H @ PAL @ 25 fps	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H, PAL	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H, PAL	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H, PAL	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H @ AHD / HD-CVI / HD-TVI @ 25 fps , 960 x 576 - 960H @ PAL	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H @ AHD / HD-CVI / HD-TVI @ 25 fps , 960 x 576 - 960H @ PAL	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H @ AHD / HD-CVI / HD-TVI @ 25 fps , 960 x 576 - 960H @ PAL	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H @ AHD / HD-CVI / HD-TVI @ 25 fps , 960 x 576 - 960H @ PAL	1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H @ AHD / HD-CVI / HD-TVI @ 25 fps , 960 x 576 - 960H @ PAL	
Lens	3.6 mm	2.8 mm	3.6 mm	2.8 mm	2.8 mm	3.6 mm	3.6 mm	3.6 mm	3.6 mm	3.6 mm	2.8 mm	3.6 mm	3.6 mm	2.8 mm	3.6 mm	3.6 mm	3.6 mm	3.6 mm	2.8 mm	2.8 mm	2.8 mm	2.8 mm	2.8 mm	2.8 mm	
S/N ratio	--	--	--	--	--	> 65 dB	> 65 dB	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	
View angle	• 83 ° (manufacturer data) • 71 ° (our tests result)	• 95 ° (manufacturer data) • 56 ° (our tests result)	• 77 ° (manufacturer data) • 70 ° (our tests result)	• 95 ° (manufacturer data) • 103 ° (our tests result)	• 95 ° (manufacturer data) • 83 ° (our tests result)	• 93 ° (manufacturer data) • 90 ° (our tests result)	• 93 ° (manufacturer data) • 90 ° (our tests result)	102 °	• 83 ° (manufacturer data) • 82 ° (our tests result)	• 83 ° (manufacturer data) • 83 ° (our tests result)	• 101 ° (manufacturer data) • 104 ° (our tests result)	83 °	102 °	• 86 ° (manufacturer data) • 82 ° (our tests result)	• 88 ° (manufacturer data) • 84 ° (our tests result)	• 83 ° (manufacturer data) • 84 ° (our tests result)	• 86 ° (manufacturer data) • 82 ° (our tests result)	• 86 ° (manufacturer data) • 82 ° (our tests result)	• 106 ° (manufacturer data) • 100 ° (our tests result)	• 106 ° (manufacturer data) • 101 ° (our tests result)	• 104 ° (manufacturer data) • 97 ° (our tests result)	• 104 ° (manufacturer data) • 97 ° (our tests result)	• 106 ° (manufacturer data) • 101 ° (our tests result)		
Range of IR illumination	25 m	30 m	30 m	30 m	30 m	30 m	30 m	30 m	30 m	30 m	30 m	40 m	40 m	40 m	80 m	80 m	25 m	25 m	20 m	20 m	90 m	90 m	30 m	40 m	
IR illuminator power adjustment	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	
Mechanical protection class	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	
Audio	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	
Video output	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI - selectable by switch	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI - selectable by switch	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI - selectable by switch	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI - selectable by switch	AHD / HD-CVI / HD-TVI / PAL, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / PAL, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	1 Vpp / 75 Ω - AHD / HD-CVI / HD-TVI / PAL, BNC socket	1 Vpp / 75 Ω - AHD / HD-CVI / HD-TVI / PAL, BNC socket	1 Vpp / 75 Ω - AHD / HD-CVI / HD-TVI / PAL, BNC socket	1 Vpp / 75 Ω - AHD / HD-CVI / HD-TVI / PAL, BNC socket	1 Vpp / 75 Ω - AHD / HD-CVI / HD-TVI / PAL, BNC socket	1 Vpp / 75 Ω - AHD / HD-CVI / HD-TVI / PAL, BNC socket	
OSD menu	✓	✓	✓	✓	✓	OSD menu available via DAHUA recorder	OSD menu available via DAHUA recorder	✓	OSD menu available via DAHUA recorder	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	OSD menu available via Hikvision HD-TVI recorder	OSD menu available via Hikvision HD-TVI recorder	OSD menu available via recorder	OSD menu available via recorder	OSD menu available via recorder	
Main features	• D-WDR - Wide Dynamic Range • DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • BLC - Back Light Compensation • Day/Night mode (color/bsw/awt) • Auto White Balance • Sharpness - sharper image outlines	• D-WDR - Wide Dynamic Range • ICR - Movable InfraRed filter • DNR - Digital Noise Reduction • AGC - Automatic Gain Control • BLC - Back Light Compensation • Day/Night mode (color/bsw/awt) • Auto White Balance • Sharpness - sharper image outlines	• D-WDR - Wide Dynamic Range • ICR - Movable InfraRed filter • DNR - Digital Noise Reduction • AGC - Automatic Gain Control • BLC - Back Light Compensation • Day/Night mode (color/bsw/awt) • Auto White Balance • Sharpness - sharper image outlines	• D-WDR - Wide Dynamic Range • DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • BLC - Back Light Compensation • Day/Night mode (color/bsw/awt) • Auto White Balance • Sharpness - sharper image outlines	• D-WDR - Wide Dynamic Range • DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • BLC - Back Light Compensation • Day/Night mode (color/bsw/awt) • Auto White Balance • Sharpness - sharper image outlines	• D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Sharpness - sharper image outlines • AGC - Automatic Gain Control • Privacy zones • Auto White Balance	• D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • Sharpness - sharper image outlines • AGC - Automatic Gain Control • Privacy zones • Auto White Balance	• Smart Dual Illumination technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • Day/night mode • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance • Sharpness - sharper image outlines	• Smart Dual Illumination technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • Day/night mode • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance • Sharpness - sharper image outlines	• D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Privacy zones - max. 8 • Mirror - Mirror image • Auto White Balance • Sharpness - sharper image outlines	• D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Privacy zones - max. 8 • Mirror - Mirror image • Auto White Balance • Sharpness - sharper image outlines	• D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Privacy zones - max. 8 • Mirror - Mirror image • Auto White Balance • Sharpness - sharper image outlines	• D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Privacy zones - max. 8 • Mirror - Mirror image • Auto White Balance • Sharpness - sharper image outlines	• D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Privacy zones - max. 8 • Mirror - Mirror image • Auto White Balance • Sharpness - sharper image outlines	• Smart Dual Illumination technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Privacy zones - max. 8 • Mirror - Mirror image • Auto White Balance • Sharpness - sharper image outlines	• WDR - 130 dB - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Privacy zones - max. 8 • Mirror - Mirror image • Auto White Balance • Sharpness - sharper image outlines	• WDR - 130 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance • Privacy zones - max. 8 • Mirror - Mirror image • Sharpness - sharper image outlines	• D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • ICR - Movable InfraRed filter • BLC - Back Light Compensation • AGC - Automatic Gain Control • Auto White Balance • Day/night mode • Sharpness - sharper image outlines	• D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • ICR - Movable InfraRed filter • BLC - Back Light Compensation • AGC - Automatic Gain Control • Auto White Balance • Day/night mode • Sharpness - sharper image outlines	• D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • ICR - Movable InfraRed filter • BLC - Back Light Compensation • AGC - Automatic Gain Control • Auto White Balance • Day/night mode • Sharpness - sharper image outlines	• D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • ICR - Movable InfraRed filter • BLC - Back Light Compensation • AGC - Automatic Gain Control • Auto White Balance • Day/night mode • Sharpness - sharper image outlines	• D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • ICR - Movable InfraRed filter • BLC - Back Light Compensation • AGC - Automatic Gain Control • Auto White Balance • Day/night mode • Sharpness - sharper image outlines			
Power supply	12 V DC / 400 mA	12 V DC / 220 mA	12 V DC / 220 mA	12 V DC / 300 mA	12 V DC / 220 mA	12 V DC / 220 mA	12 V DC / 220 mA	12 V DC / 235 mA	12 V DC / 220 mA	12 V DC / 220 mA	12 V DC / 275 mA	12 V DC / 410 mA	12 V DC / 230 mA	12 V DC / 230 mA	12 V DC / 250 mA	12 V DC / 440 mA	12 V DC / 340 mA	12 V DC / 430 mA	12 V DC / 430 mA	12 V DC / 250 mA	12 V DC / 180 mA	12 V DC / 280 mA	12 V DC / 280 mA	12 V DC / 330 mA	
Power consumption	≤ 4.8 W	≤ 2.6 W	≤ 2.6 W	≤ 3.6 W	≤ 2.6 W	≤ 2.7 W	≤ 2.6 W	≤ 2.8 W	≤ 2.6 W	≤ 2.6 W	≤ 3.3 W	≤ 4.9 W	≤ 2.8 W	≤ 3 W	≤ 3.1 W	≤ 4.1 W	≤ 4.1 W	≤ 5.1 W	≤ 3 W	≤ 2.2 W	≤ 3.4 W	≤ 3.4 W	≤ 3.4 W	≤ 3.9 W	
Housing	Compact - Aluminum	Compact - Aluminum	Compact - Aluminum	Compact - Plastic	Compact - Plastic	Compact, Plastic	Compact, Aluminum	Compact, Plastic	Compact, Plastic	Compact - Metal	Compact, Metal	Compact, Plastic + Metal	Compact, Plastic	Compact, Plastic	Compact, Plastic	Compact, Plastic / Metal	Compact Plastic + Metal	Compact, Plastic + Metal	Compact, Metal	Compact, Metal	Compact, Plastic	Compact, Metal	Compact, Metal	Compact - Metal + Plastic	
Vandal-proof	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	
Color	White	White	White	White + Black	White	White	White	White + Black	White	White	White + Black	White	White	White	White	White	White	White	White	White	White + Black	White + Black	White + Black	White + Black	
"Index of Protection"	IP67	IP67	IP67	IP66	IP67	IP67	IP67	IP67	IP67	IP67	IP67	IP67	IP67	IP67	IP67	IP67	IP67	IP67	IP67	IP67	IP67	IP67	IP67	IP67	
SAP Code	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	
Operation temp	-10 °C ... 60 °C	-20 °C ... 60 °C	-20 °C ... 60 °C	-20 °C ... 60 °C	-20 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	-40 °C ... 60 °C	
Weight	0.3 kg	0.39 kg	0.39 kg	0.16 kg	0.19 kg	0.14 kg	0.25 kg	0.17 kg	0.18 kg	0.33 kg	0.34 kg	0.41 kg	0.22 kg	0.22 kg	0.28 kg	0.3 kg	0.29 kg	0.65 kg	0.26 kg	0.65 kg	0.15 kg	0.34 kg	0.56 kg	0.33 kg	
Dimensions	157 x 66 x 68 mm	172 x 73 x 73 mm	172 x 73 x 73 mm	162 x 70 x 70 mm	174 x 70 x 68 mm	149 x 70 x 70 mm	158 x 70 x 70 mm	161 x 70 x 70 mm	163 x 70 x 70 mm	167 x 70 x 70 mm	175 x 71 x 72 mm	91 x 90 x 241 mm	199 x 76 x 80 mm	80 x 76 x 199 mm	198 x 80 x 76 mm	241 x 91 x 90 mm	198 x 80 x 76 mm	241 x 91 x 90 mm	198 x 80 x 76 mm	241 x 91 x 90 mm	198 x 80 x 76 mm	241 x 91 x 90 mm	198 x 80 x 76 mm	241 x 91 x 90 mm	
Supported languages	English	Polish, English, French, Spanish, Portuguese, Russian, Italian	Polish, English, French, Spanish, Portuguese, Russian, Italian	Polish, English, French, Spanish, Portuguese, Russian, Italian	Polish, English	--	--	--	--	--	--	--	--	--	--	--	--	--	--	Polish, English	Polish, English	English	English	English	
Manufacturer / Brand	APTI	APTI	APTI	APTI	APTI	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	Hikvision	Hikvision	Hikvision	Hikvision	Hikvision	
Guarantee	2 years	2 years</																							