

Code: HYBRO-41

AHD, PAL, TCP/IP DVR **HYBRO-41** 4 CHANNELS

Net: **58.85 EUR** Gross: **58.85 EUR**

The HYBRO-41 digital recorder with AHD (Analog High Definition) and PAL interface is a professional device applicable in surveillance systems. The AHD interface allows to transmission of analog video signal via coaxial cable in 720p resolution. The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.



SPECIFICATION

Standard:	AHD, PAL, TCP/IP
Video inputs:	4 pcs BNC - AHD, CVBS
Video outputs:	1 pcs HDMI 1 pcs VGA
Audio inputs:	1 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.264
Number of compression levels:	6
Image records resolutions:	AHD-NH (960 x 1080) AHD-M (1280 x 720) AHD-L, PAL (928 x 576) PAL (704 x 576) IP (1920 x 1080) IP 1280 x 960) IP (1280 x 720)
Maximal total frame rate:	AHD : 48 fps @ 960 x 1080 px, AHD 100 fps @ 1280 x 720 px, AHD, PAL 100 fps @ 928 x 576 px, AHD, PAL 100 fps @ 704 x 576 px, IP : 100 fps @ 1920 x 1080 px, IP : 200 fps @ 1280 x 960 px, IP : 200 fps @ 1280 x 720 px
Recording speed adjustment:	1 ... 12 fps @ 960 x 1080 px 1 ... 25 fps @ 1280 x 720 px 1 ... 25 fps @ 928 x 576 px 1 ... 25 fps @ 704 x 576 px for each channel
Operation modes:	• 4 x AHD-NH • 4 x AHD-M • 4 x AHD-L / PAL • 2 x AHD-M + 2 x IP 720p • 4 x IP 1080p • 8 x IP 960p • 8 x IP 720p The 4 x AHD-NH mode allows for any combination of the AHD-H, AHD-M, PAL cameras, eg.: 1 x AHD-H + 2 x AHD-M + 1 x PAL
Recording modes:	Manual, Motion Detection, Schedule
Supported hard drives:	1 x 8 TB SATA

External storage devices backup:	Records backup at (.avi) format to USB (pendrive)
Searching and playback the records:	Records searching: timeline or file list. Playback: forward, fast, slow. Playback max. 4 cameras in the same time
Network functions:	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters
Mobile phones support:	Port no.: 34567 or access by a cloud (P2P) • Android: Free application XMEye • iOS (iPhone): Free application XMEye
Alarm inputs / outputs:	—
PTZ control:	RS-485 - PELCO-D/P and others
Motion Detection:	Split the screen into zones : 16 x 12 motion zones
Mouse support:	✓
IR remote controller in the set:	—
Power supply:	12 V DC / 2.5 A (power adapter included)
Color:	Black
Weight:	0.458 kg
Dimensions:	234 x 211 x 49 mm
Supported languages:	English, Bulgarian, Czech, French, Finnish, Greek, Spanish, Dutch, German, Polish, Portuguese, Russian, Romanian, Slovak, Swedish, Turkish, Hungarian, Vietnamese, Italian
Country of origin:	China
Guarantee:	2 years

PRESENTATION

Front view:



Rear view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



In the kit:



OUR OPINIONS



- In mode 4 x AHD-NH the AHD-H 1080p cameras are recorded in 960 x 1080 px resolution.
- The recorder does not support the ONVIF protocol in IP cameras operating modes.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60