

Code: DS-7204HTHI-K1

AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR **DS-7204HTHI-K1** 4 CHANNELS

Hikvision

Net: **284.55 EUR** Gross: **284.55 EUR**

The DS-7204HTHI-K1 digital recorder with AHD (Analog High Definition), HD-CVI (High Definition Composite Video Interface), HD-TVI (High Definition Transport Video Interface), TCP/IP and CVBS interface is a professional device applicable in surveillance systems.

The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.



SPECIFICATION

| | |
|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standard: | AHD, HD-CVI, HD-TVI, CVBS, TCP/IP |
| Video inputs: | 4 pcs BNC - AHD / HD-CVI / HD-TVI / CVBS |
| Video outputs: | 1 pcs HDMI 4K 1 pcs VGA 1 pcs CVBS - BNC socket |
| Audio inputs: | 4 pcs CINCH |
| Audio outputs: | 1 pcs CINCH |
| Image compression method: | H.265 / H.265+ / H.264 / H.264+ |
| Image records resolutions: | <ul style="list-style-type: none">• HD-TVI : 8 Mpx - 3840 x 2160 , 5 Mpx - 2592 x 1944 , 4 Mpx - 2560 x 1440 , 3 Mpx - 1920 x 1536 , 1080p - 1920 x 1080 , 720p - 1280 x 720• AHD : 5 Mpx - 2592 x 1944 , 4 Mpx - 2560 x 1440 , 3 Mpx - 1920 x 1536 , 1080p - 1920 x 1080 , 720p - 1280 x 720• HD-CVI : 4 Mpx - 2560 x 1440 , 1080p - 1920 x 1080 , 720p - 1280 x 720• CVBS : 960H - 960 x 576• IP : max. 8 Mpx - 3840 x 2160 |

| | |
|-------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Recording speed adjustment: | 8 Mpx IP @ 1 ... 25 fps 8 Mpx @ 1 ... 12 fps 5 Mpx @ 1 ... 20 fps 4 Mpx @ 1 ... 25 fps 3 Mpx @ 1 ... 18 fps 1080p @ 1 ... 25 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps for each channel |
| Operation modes: | Firmware V3.5.37 build 180801 • 4 x HD-TVI / AHD / HD-CVI / PAL / IP + 2 x IP |
| Recording modes: | Manual, Motion Detection, Schedule |
| Supported hard drives: | 1 x 10 TB SATA |
| External storage devices backup: | Backup to USB drive (pendrive, external drive) |
| Searching and playback the records: | Records searching: timeline or file list. Playback: forward, fast, slow. Playback max. 4 cameras in the same time |
| Network interface: | 1 x RJ-45 - 10/100/1000 Base-TX |
| Bitrate: | 32 Mbps |
| Network functions: | Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters |
| Network protocols: | TCP/IP, PPPoE, DHCP, Hik Cloud P2P, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP, HTTPS, ONVIF |
| Mobile phones support: | Port no.: 8000 or access by a cloud (P2P) Android: Free application iVMS-4500 iOS (iPhone): Free application iVMS-4500 |
| Default IP address: | DHCP or 192.168.1.64 |
| Default admin user / password: | admin / - |
| Web browser access ports: | 80 |
| PC client access ports: | 554 RTSP, 8000 |
| Mobile client access ports: | 8000 |
| Port ONVIF: | 80 |
| RTSP URL: | <ul style="list-style-type: none"> • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream |
| Alarm inputs / outputs: | 4 / 1 |
| PTZ control: | RS-485 PELCO-D/P Control compatible with coax HD-TVI Hikvision |
| Motion Detection: | Split the screen into zones : 22 x 18 motion zones |
| USB: | <ul style="list-style-type: none"> • 1 pcs USB 3.0 • 1 pcs USB 2.0 |
| Mouse support: | ✓ |
| IR remote controller in the set: | — |
| Main features: | Intelligent image analysis : intrusion, crossing the line (tripwire), scene changing |
| Power supply: | 12 V DC / 2 A (power adapter included) |
| Color: | Black |
| Weight: | 1.24 kg |
| Dimensions: | 315 x 250 x 47 mm |



| | |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Supported languages: | Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Greek, Spanish, Dutch, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian |
| Manufacturer / Brand: | Hikvision |
| SAP Code: | 300220515 |
| Guarantee: | 3 years |

PRESENTATION

Front panel:



Rear view:



See how to mount a hard disk drive and configure the recorder:

:

In the kit:



PACKAGE

| | |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|