

Code: APTI-NX1601-S3

# AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR **APTI-NX1601-S3** 16 CHANNELS

Net: **105.39 EUR** Gross: **105.39 EUR**

The APTI-NX1601-S3 digital recorder with AHD (Analog High Definition), HD-CVI (High Definition Composite Video Interface), HD-TVI (High Definition Transport Video Interface), TCP/IP and CVBS interface is a professional device applicable in surveillance systems.

The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.



## SPECIFICATION

Standard:	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP
Video inputs:	16 pcs BNC
Video outputs:	1 pcs HDMI 1 pcs VGA 1 pcs CVBS
Audio inputs:	2 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.264
Number of compression levels:	6
Image records resolutions:	<ul style="list-style-type: none"><li>• AHD / HD-CVI / HD-TVI : 1080N - 960 x 1080, 720p - 1280 x 720</li><li>• CVBS : 960H - 960 x 576,</li><li>• IP : 1080p - 1920 x 1080</li></ul>
Recording speed adjustment:	1080p IP @ 1 ... 25 fps 1080N @ 1 ... 12 fps 720p @ 1 ... 12 fps 960H @ 1 ... 12 fps for each channel
Operation modes:	<ul style="list-style-type: none"><li>• 16 x AHD / HD-CVI / HD-TVI / CVBS @ 1080N</li><li>• 14 x ... 2 x AHD / HD-CVI / HD-TVI / CVBS @ 1080N + 2 x ... 14 x IP @ 1080p</li><li>• 16 x IP @ 1080p</li></ul> All modes allow for any combination of the AHD-H, HD-CVI, HD-TVI, PAL cameras
Recording modes:	Motion Detection, Schedule
Supported hard drives:	1 x 6 TB SATA
External storage devices backup:	Records backup at (.avi) format to USB (pendrive)
Searching and playback the records:	Records searching: timeline or file list. Playback: forward, backward, fast, slow. Records playback from max. 4 channels in the same time
Network functions:	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters
Mobile phones support:	Port no.: 554 or access by a cloud (P2P) <ul style="list-style-type: none"><li>• Android: Free application <a href="#">FREEIP PRO</a>, Android: Free application <a href="#">FREEIP</a></li><li>• iOS (iPhone): Free application <a href="#">FREEIP PRO</a>, iOS (iPhone): Free application <a href="#">FREEIP</a></li></ul>
Default IP address:	192.168.1.88

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

Default admin user / password:	admin / 12345
Web browser access ports:	80, 5000, 554
PC client access ports:	80, 5000, 554
Mobile client access ports:	80, 5000, 554
Port ONVIF:	80
USB:	2 pcs USB 2.0
Alarm inputs / outputs:	—
PTZ control:	RS-485 - PELCO-D/P
Motion Detection:	Split the screen into zones : 22 x 18 motion zones
Mouse support:	✓
IR remote controller in the set:	—
Power supply:	12 V DC / 2 A (power adapter included)
Color:	Black
Weight:	0.95 kg
Dimensions:	260 x 245 x 45 mm
Supported languages:	Polish, English, Bulgarian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Turkish, Hungarian, Italian
Country of origin:	China
Manufacturer / Brand:	APTI
Guarantee:	2 years

## PRESENTATION

Front panel:



Rear view:



In the kit:



Configuration and operation of the FreeIP cloud:  
:

#### PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

