

	AHD, HD-CVI, HD-TVI CAMERA APTI-H50V3-2812 2Mpx / 5Mpx 2.8 ... 12 mm	AHD, HD-CVI, HD-TVI CAMERA APTI- H50V31-2812W 2Mpx / 5Mpx 2.8 ... 12 mm	AHD, HD-CVI, HD-TVI, CVBS CAMERA APTI- H52V31-2812W 8.3 Mpx 4K UHD 2.8 ... 12 mm	AHD, HD-CVI, HD-TVI, CVBS CAMERA APTI- H83V31-2812W 8.3 Mpx 4K UHD 2.8 ... 12 mm	AHD, HD-CVI, HD-TVI, PAL VANDAL PROOF CAMERA HAC83V31-2812W 2-2712-S2 -5 Mpx 2.7 ... 12 mm - MOTOZOOM DAHUA	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HDW1500T2- A27135-S2 - 5 Mpx 2.7 ... 12 mm - MOTOZOOM DAHUA	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HDW1801T2- A27135-S2 - 8.3 Mpx 2.7 ... 13.5 mm - MOTOZOOM DAHUA	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HDW2501T2- A27135-S2 - 8.3 Mpx 3.7 ... 11 mm - MOTOZOOM DAHUA	AHD, HD-CVI, HD-TVI, PAL CAMERA HAC-HDW280T2- Z-A3711 - 8.3 Mpx 3.7 ... 11 mm - MOTOZOOM DAHUA	AHD, HD-CVI, HD-TVI, CVBS CAMERA DS-2CE79H0T- IT13ZF2-7.13.5mm(CI) - 5 Mpx Hikvision	AHD, HD-CVI, HD-TVI, PAL CAMERA BCS- DM30803IR3-B - 8.3 Mpx 4K UHD 3.3 ... 12 mm - MOTOZOOM	AHD, HD-CVI, HD-TVI, PAL CAMERA BCS-EA45VR4H2I- -5 Mpx 3.3 ... 12 mm	AHD, HD-CVI, HD-TVI, PAL CAMERA BCS-EA48VR6G2I- -8 Mpx 2.7 ... 13.5 mm - MOTOZOOM	AHD, HD-CVI, HD-TVI, PAL CAMERA BCS-EA48VR6G- G2I2 - 8 Mpx 4K UHD 2.7 ... 13.5 mm - MOTOZOOM	AHD, HD-CVI, HD-TVI, PAL CAMERA BCS-EA55VSR4- G2I2 - 5 Mpx 2.8 ... 12 mm - MOTOZOOM	AHD, HD-CVI, HD-TVI, PAL CAMERA BCS- EA58VSR4H2I - 8 Mpx 4K UHD 3.6 ... 10 mm - MOTOZOOM	AHD, HD-CVI, HD-TVI, PAL CAMERA BCS-EA58VSR4- G2I2 - 8 Mpx 4K UHD 3.6 ... 10 mm - MOTOZOOM
																	
	46.06 EUR 46.06 EUR	44.52 EUR 44.52 EUR	60.00 EUR 60.00 EUR	75.10 EUR 75.10 EUR	140.08 EUR 140.08 EUR	140.08 EUR 140.08 EUR	205.40 EUR 205.40 EUR	216.78 EUR 216.78 EUR	320.57 EUR 320.57 EUR	127.02 EUR 127.02 EUR	175.40 EUR 175.40 EUR	52.02 EUR 52.02 EUR	129.44 EUR 129.44 EUR	129.44 EUR 129.44 EUR	78.63 EUR 78.63 EUR	111.05 EUR 111.05 EUR	111.05 EUR 111.05 EUR
Standard	AHD, HD-CVI, HD-TVI	AHD, HD-CVI, HD-TVI	AHD, HD-CVI, HD-TVI, CVBS	AHD, HD-CVI, HD-TVI, CVBS	AHD / HD-CVI / HD-TVI / CVBS	AHD, HD-CVI, HD-TVI, CVBS	AHD, HD-CVI, HD-TVI, CVBS	AHD, HD-CVI, HD-TVI, PAL	AHD, HD-CVI, HD-TVI, CVBS	AHD, HD-CVI, HD-TVI, CVBS	AHD / HD-CVI / HD-TVI / CVBS	AHD / HD-CVI / HD-TVI / CVBS	AHD / HD-CVI / HD-TVI / CVBS	AHD / HD-CVI / HD-TVI / CVBS	AHD / HD-CVI / HD-TVI / CVBS	AHD / HD-CVI / HD-TVI / CVBS	AHD / HD-CVI / HD-TVI / CVBS
Matrix size	5 Mpx	5 Mpx	8.3 Mpx	8.3 Mpx	5 Mpx	5 Mpx	8.3 Mpx	5 Mpx	8 Mpx	5 Mpx	8.3 Mpx	-	8 Mpx	-	-	-	-
IR illuminator support	-	-	-	-	-	ICR - Movable InfraRed filter	-	-	-	-	-	-	ICR - Movable InfraRed filter	-	-	-	-
Sensor	1/2.7" CMOS	1/2.7" CMOS	1/2.5" Sony CMOS	1/2.8" SONY Starvis™ Back illuminated CMOS	1/2.7" Progressive Scan CMOS	1/2.7" Progressive Scan CMOS	Progressive Scan CMOS	1/2.7" Progressive Scan CMOS	1/1.8" Progressive Scan CMOS	Progressive Scan CMOS	1/2.5" SONY Starvis™ CMOS	1/2.5" CMOS	1/2.7" Progressive Scan CMOS	1/2.7" CMOS	1/2.8" CMOS	1/1.8" CMOS	1/1.8" CMOS
Resolution	2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps, 12.5 fps, 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 25 fps, 30 fps 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI	2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps, 12.5 fps, 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 25 fps, 30 fps 1920 x 1080 - 1080p @ AHD / HD-CVI / HD-TVI	• 3840 x 2160 - 8.3 Mpx 4K UHD @ AHD / HD-CVI / HD-TVI @ 12.5 fps, 15 fps • 2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps, 12.5 fps, 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 25 fps, 30 fps • 1920 x 1080 - 1080p @ AHD / HD-TVI / HD-CVI @ 25 fps, 30 fps • 960 x 576 - 960H @ PAL	3840 x 2160 - 8.3 Mpx 4K UHD @ AHD, 15 fps, 3840 x 2160 - 8.3 Mpx 4K UHD @ HD-CVI / HD-TVI, 15 fps / 12.5 fps 2592 x 1944 - 5 Mpx @ AHD / HD-TVI, 20 fps / 12.5 fps, 2560 x 1440 - 4 Mpx @ AHD, 30 fps / 25 fps / 15 fps 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 25 fps, 30 fps 1920 x 1080 - 1080p @ AHD / HD-TVI / HD-CVI @ 25 fps, 30 fps 1920 x 1080 - 1080p @ AHD / HD-TVI / HD-CVI @ 25 fps, 30 fps • 960 x 576 - 960H @ PAL	2880 x 1620 - 5 Mpx @ AHD / HD-CVI only, Aspect Ratio 16 : 9 2592 x 1944 - 5 Mpx @ AHD / HD-TVI only, Aspect Ratio 16 : 9 2560 x 1440 - 4 Mpx @ AHD, 30 fps / 25 fps / 15 fps 2560 x 1440 - 4 Mpx @ AHD / HD-TVI only, Aspect Ratio 16 : 9 1920 x 1080 - 1080p @ AHD / HD-TVI only, Aspect Ratio 16 : 9 960 x 576 - 960H, PAL	2880 x 1620 - 5 Mpx, HD-CVI only, Aspect Ratio 16 : 9 2592 x 1944 - 5 Mpx, HD-CVI only, Aspect Ratio 16 : 9 2560 x 1440 - 4 Mpx @ AHD, 30 fps / 25 fps / 15 fps 2560 x 1440 - 4 Mpx @ AHD / HD-TVI only, Aspect Ratio 16 : 9 1920 x 1080 - 1080p @ AHD / HD-TVI only, Aspect Ratio 16 : 9 960 x 576 - 960H, PAL	• HD-CVI : 3840 x 2160 - 8.3 Mpx 4K UHD 2880 x 1920 - 6 Mpx 2560 x 1440 - 3.7 Mpx • HD-TVI : 2880 x 1620 - 5 Mpx 2560 x 1440 - 3.7 Mpx • CVBS : 960 x 576 - 960H	2560 x 1944 - 5 Mpx @ AHD / HD-TVI, 20 fps 2560 x 1440 - 4 Mpx @ AHD / HD-TVI / HD-CVI @ 25 fps, 30 fps 1920 x 1080 - 1080p @ AHD / HD-TVI, 25 fps 960 x 576 - 960H @ CVBS	3840 x 2160 - 8.3 Mpx 4K UHD @ AHD / HD-CVI / HD-TVI, 15 fps / 12.5 fps, 2704 x 1950 - 5 Mpx @ AHD / HD-TVI @ 20 fps, 2560 x 1440 - 4 Mpx @ AHD / HD-CVI / HD-TVI @ 25 fps, 30 fps 1920 x 1080 - 1080p @ AHD / HD-TVI / HD-CVI @ 25 fps, 30 fps 1280 x 720 - 720p @ AHD / HD-CVI / HD-TVI, 25 fps / 30 fps	2704 x 1950 - 5 Mpx @ AHD / HD-TVI @ 20 fps, 2560 x 1440 - 4 Mpx @ AHD / HD-TVI / HD-CVI @ 25 fps, 30 fps 1920 x 1080 - 1080p @ AHD / HD-TVI / HD-CVI @ 25 fps, 30 fps 960 x 576 - 960H @ CVBS	• AHD / HD-CVI / HD-TVI : 3840 x 2160 - 8 Mpx / 15 fps 2592 x 1944 - 5 Mpx / 25 fps 2560 x 1440 - 4 Mpx / 25 fps 1920 x 1080 - 1080p / 25 fps • CVBS : 960 x 576 - 960H	3840 x 2160 - 8 Mpx 4K UHD @ AHD / HD-TVI / HD-CVI, 15 fps 2560 x 1440 - 4 Mpx @ AHD / HD-TVI / HD-CVI, 30 fps / 25 fps 1920 x 1080 - 1080p @ AHD / HD-TVI / HD-CVI, 30 fps / 25 fps 960 x 576 - 960H @ CVBS	2592 x 1944 - 5 Mpx @ AHD / HD-TVI, 20 fps 2560 x 1440 - 4 Mpx @ AHD / HD-TVI / HD-CVI, 25 fps 1920 x 1080 - 1080p @ AHD / HD-TVI / HD-CVI, 25 fps 960 x 576 - 960H @ CVBS	3840 x 2160 - 8 Mpx 4K UHD @ AHD / HD-TVI / HD-CVI, 15 fps 2560 x 1440 - 4 Mpx @ AHD / HD-TVI / HD-CVI, 30 fps / 25 fps 960 x 576 - 960H @ CVBS	3840 x 2160 - 8 Mpx 4K UHD @ AHD / HD-TVI / HD-CVI, 15 fps 2560 x 1440 - 4 Mpx @ AHD / HD-TVI / HD-CVI, 30 fps / 25 fps 960 x 576 - 960H @ CVBS		
Range of IR illumination	30 m	30 m	30 m	30 m	30 m	60 m	60 m	60 m	60 m	40 m	40 m	40 m	60 m	60 m	40 m	40 m	40 m
IR illuminator power adjustment	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	Automatic	-	Automatic	-	-	-	-
S/N ratio	-	-	≥ 50 dB	-	-	> 65 dB	-	> 65 dB	-	-	-	-	-	-	-	-	-
Lens	2.8 ... 12 mm	2.8 ... 12 mm	2.8 ... 12 mm	2.8 ... 12 mm	2.7 ... 12 mm - Motozoom - The camera does not have auto-focus function	2.7 ... 12 mm - Motozoom - The camera does not have auto-focus function	2.7 ... 13.5 mm - Motozoom, AutoFocus	2.7 ... 13.5 mm - Motozoom	3.7 ... 11 mm - Motozoom	2.7 ... 13.5 mm - Motozoom	3.3 ... 12 mm Motozoom, AutoFocus	3.3 ... 12 mm	2.7 ... 13.5 mm - Motozoom	2.7 ... 13.5 mm - Motozoom	2.8 ... 12 mm - Motozoom	3.6 ... 10 mm - Motozoom	3.6 ... 10 mm - Motozoom
View angle	• 88 ° ... 31 ° (manufacturer data) • 93 ° ... 35 ° (our tests result)	• 88 ° ... 31 ° (manufacturer data) • 87 ° ... 34 ° (our tests result)	• 92 ° ... 27 ° (manufacturer data) • 94 ° ... 37 ° (our tests result)	• 87 ° ... 24 ° (manufacturer data) • 85 ° ... 34 ° (our tests result)	• 107 ° ... 34 ° (manufacturer data) • 102 ° ... 35 ° @ HD-CVI (our tests result) • 87 ° ... 34 ° (our tests result) • 88 ° ... 30 ° @ AHD / HD-TVI (our tests result)	• 107 ° ... 34 ° (manufacturer data) • 102 ° ... 35 ° @ HD-CVI (our tests result) • 87 ° ... 34 ° (our tests result) • 88 ° ... 30 ° @ AHD / HD-TVI (our tests result)	• 114 ° ... 32 ° (manufacturer data) • 110 ° ... 32 ° @ HD-CVI, 94 ... 29 ° @ AHD, HD-TVI (our tests result)	• 113 ° ... 31 ° (manufacturer data) • 105 ° ... 46 ° (our tests result)	• 112 ° ... 46 ° (manufacturer data) • 105 ° ... 46 ° (our tests result)	• 95 ° ... 26 ° (manufacturer data) • 93 ... 25 (our tests result)	• 90 ° ... 31 ° (manufacturer data) • 98 ... 32 ° (our tests result)	120 ° ... 38 °	114 ° ... 32 °	114 ° ... 32 °	124 ° ... 36 °	123 ° ... 48 °	123 ° ... 48 °
Audio	-	-	-	-	-	Microphone built-in - HD-CVI only	Microphone built-in - HD-CVI only	• Microphone built-in, • Audio support via coaxial cable - HD-CVI only	• Microphone built-in - HD-CVI only	-	-	-	• Microphone built-in	✓	Microphone built-in	Microphone built-in	Microphone built-in
Mechanical protection class	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
SAP Code	-	-	-	-	-	-	-	-	300615088	-	-	-	-	-	-	-	-
Video output	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI - Via OSD, selectable by switch	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI - Via OSD, selectable by switch	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI / PAL - selectable by switch	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI / CVBS - selectable by switch	AHD / HD-CVI / HD-TVI / PAL - 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS - 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS - 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS - 1 Vpp / 75 Ω	1 x AHD / HD-CVI / HD-TVI / CVBS - 1 Vpp / 75 Ω, BNC socket	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Main features	• D-WDR - Wide Dynamic Range • DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance • Day/Night mode - configurable • Sharpness - sharper image outlines	• D-WDR - Wide Dynamic Range • DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance • Day/Night mode - configurable • Sharpness - sharper image outlines	• D-WDR - Wide Dynamic Range • DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance • Day/Night mode - configurable • Sharpness - sharper image outlines	• D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance • Day/Night mode - configurable • Sharpness - sharper image outlines	• D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance • Day/Night mode - configurable • Sharpness - sharper image outlines • Privacy zones - max. 8 • Mirror - Mirror image	• Motozoom lens - The control possible only from Dahua recorders in HD-CVI mode • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • F-DNR (Defog) - Reduction of image noise caused by precipitation • BLC/HLC - Back Light / High Light Compensation • Auto White Balance • AGC - Automatic Gain Control • D-ZOOM - Digital Zoom • Mirror - Mirror image • Sharpness - sharper image outlines • Privacy zones - max. 8	• Motozoom lens - The control possible only from Dahua recorders in HD-CVI mode • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • F-DNR (Defog) - Reduction of image noise caused by precipitation • BLC/HLC - Back Light / High Light Compensation • Auto White Balance • AGC - Automatic Gain Control • Mirror - Mirror image • Sharpness - sharper image outlines • D-ZOOM - Digital Zoom : 4 x • Privacy zones - max. 8	• Motozoom lens - The control possible only from Dahua recorders in HD-CVI mode • WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • F-DNR (Defog) - Reduction of image noise caused by precipitation • BLC/HLC - Back Light / High Light Compensation • Auto White Balance • AGC - Automatic Gain Control • Mirror - Mirror image • Sharpness - sharper image outlines • D-ZOOM - Digital Zoom : 4 x • Privacy zones - max. 8	• Motozoom lens • D-WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • EXIR - high-efficiency infrared LEDs technology, which evenly covers the whole plan of both central vantage points of the scene as well as the corners • BLC - Back Light Compensation • AGC - Automatic Gain Control • ICR - Movable InfraRed filter • Mirror - Mirror image • Sharpness - sharper image outlines • Mirror - Mirror image	• Motozoom lens, AutoFocus • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ICR - Movable InfraRed filter • Day/night mode • Auto White Balance • AGC - Automatic Gain Control • AES - Auto Electronic Shutter • Motion Detection - max. 4 zones • Privacy zones - max. 16	• Motozoom lens • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ICR - Movable InfraRed filter • Day/night mode • Auto White Balance • AGC - Automatic Gain Control • ICR - Movable InfraRed filter • Auto White Balance • AGC - Automatic Gain Control • Mirror - Mirror image • Sharpness - sharper image outlines	• Motozoom lens • WDR - 120 dB - Wide Dynamic Range • 2D-DNR, 3D-DNR - Digital Noise Reduction • F-DNR (Defog) - Reduction of image noise caused by precipitation • ICR - Movable InfraRed filter • Day/night mode • Auto White Balance • AGC - Automatic Gain Control • ICR - Movable InfraRed filter • Auto White Balance • AGC - Automatic Gain Control • Mirror - Mirror image • Sharpness - sharper image outlines	• WDR - 120 dB - Wide Dynamic Range • Auto White Balance • AGC - Automatic Gain Control • Day/night mode • ICR - Movable InfraRed filter	• WDR - 120 dB - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • BLC/HLC - Back Light / High Light Compensation • Auto White Balance • AGC - Automatic Gain Control • Day/night mode • ICR - Movable InfraRed filter	• D-WDR - Wide Dynamic Range • Auto White Balance • AGC - Automatic Gain Control • Day/night mode • ICR - Movable InfraRed filter	• D-WDR - Wide Dynamic Range • Auto White Balance • AGC - Automatic Gain Control • Day/night mode • ICR - Movable InfraRed filter	
OSD menu	✓	✓	✓	✓	OSD menu available via DAHUA recorder	OSD menu available via DAHUA recorder	OSD menu available via DAHUA recorder	OSD menu available via DAHUA recorder	OSD menu available via DAHUA recorder	✓	✓	✓	OSD menu available via recorder	✓	✓	✓	✓
Housing	Dome - Metal	Dome - Metal	Dome - Metal	Dome - Metal	Dome, Metal	Dome, Aluminum	Dome, Metal	Dome, Metal	Dome, Metal	Dome, Metal	Dome, Metal	Dome, Metal	Dome, Metal	Dome, Metal	Dome, Metal	Dome, Metal	Dome, Metal
Color	Graphite	White	White	White	White	White	White	White	White	White	White	White	White	White	White	White	White
Power supply	12 V DC / 400 mA	12 V DC / 750 mA	12 V DC / 390 mA	12 V DC / 390 mA	12 V DC / 460 mA	12 V DC / 550 mA	12 V DC / 660 mA	12 V DC / 660 mA	12 V DC / 800 mA	12 V DC / 520 mA	12 V DC / 500 mA	12 V DC / 670 mA	12 V DC / 660 mA	12 V DC / 670 mA	12 V DC / 840 mA	12 V DC / 840 mA	12 V DC / 840 mA
"Index of Protection"	IP66	IP67	IP66	IP67	IP67	IP67	IP67	IP67	IP67	IP67	IP66	IP66	IP67	IP67	IP66	IP66	IP66
Power consumption	≤ 4.8 W	≤ 9 W	≤ 4.7 W	≤ 9 W	≤ 5.5 W	≤ 6.6 W	≤ 7.9 W	≤ 6.2 W	≤ 9.5 W	≤ 6.2 W	≤ 6 W	≤ 8 W	≤ 8 W	≤ 8 W	≤ 10 W	≤ 10 W	≤ 10 W
Vandal-proof	-	-	-	-	IK10	-	-	-	-	-	-	-	-	-	-	-	-
Operation temp	20 °C ... 60 °C	20 °C ... 60 °C	20 °C ... 50 °C	10 °C ... 60 °C	20 °C ... 60 °C	30 °C ... 60 °C	30 °C ... 60 °C	30 °C ... 60 °C	40 °C ... 60 °C	30 °C ... 60 °C	30 °C ... 60 °C	30 °C ... 60 °C	30 °C ... 60 °C	30 °C ... 60 °C	30 °C ... 60 °C	20 °C ... 60 °C	20 °C ... 60 °C
Weight	0.55 kg	0.55 kg	0.56 kg	0.56 kg	0.44 kg	0.57 kg	0.59 kg	0.61 kg	0.6 kg	0.59 kg	0.55 kg	0.600 kg	0.53 kg	0.53 kg	0.5 kg	0.5 kg	0.5 kg
Dimensions	Ø 120 x 100 mm	Ø 120 x 100 mm	Ø 120 x 83 mm	Ø 120 x 98 mm	Ø 122 x 89 mm	Ø 122 x 104 mm	Ø 122 x 105 mm	Ø 122 x 105 mm	Ø 122 x 107 mm	134 x 124 x 110 mm	Ø 119 x 104 mm	Ø 119 x 98 mm	Ø 122 x 104 mm	Ø 122 x 105 mm	Ø 119 x 98 mm	Ø 119 x 98 mm	Ø 119 x 98 mm
Supported languages	Polish, English, French, Spanish, Portuguese, Russian, Italian	Polish, English, French, Spanish, Portuguese, Russian, Italian	Polish, English, French, Spanish, Portuguese, Russian, Italian	Polish, English, French, Spanish, Portuguese, Russian, Italian	English, Spanish, Portuguese	-	-	-	-	English	Polish, English	Polish, English	-	Polish, English	Polish, English	Polish, English	Polish, English
Manufacturer / Brand	APTI	APTI	APTI	APTI	DAHUA	DAHUA	DAHUA	DAHUA	DAHUA	Hikvision	BCS UNIVERSAL	BCS UNIVERSAL	BCS UNIVERSAL	BCS UNIVERSAL	BCS UNIVERSAL	BCS UNIVERSAL	BCS UNIVERSAL
Guarantee	2 years	2 years	2 years	2 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3 years	3				

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00