

Code: HAC-HDBW1400R-VF-27135

HD-CVI, PAL VANDALPROOF CAMERA HAC-HDBW1400R-VF-27135 -
3.7 Mpx, 2.7 ... 13.5 mm DAHUA
Net: **89.26 GBP** Gross: **89.26 GBP**

Megapixel camera with 1/3" CMOS sensor and HD-CVI (High Definition Composite Video Interface) / PAL. The HD-CVI interface allows to transmission of analog, composite video signal via coaxial cable. It enables the transmission of HD resolution images for even 500 m distance with keeping the low costs of the installation. During transmission there are no delays and is maintained the original, high quality image.



SPECIFICATION

Standard:	HD-CVI, PAL
Sensor:	1/3 " Progressive Scan CMOS
Matrix size:	4.1 Mpx
Resolution:	2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p 960 x 576 - 960H, PAL
Video output:	HD-CVI / CVBS, 1 Vpp / 75 Ω
Lens:	2.7 ... 13.5 mm
View angle:	• 98 ° ... 26 ° (manufacturer data) • 92 ° ... 26 ° (our tests result)
Range of IR illumination:	30 m
IR illuminator support:	ICR - Movable InfraRed filter
IR illuminator power adjustment:	Automatic
S/N ratio:	> 65 dB
OSD menu:	OSD menu available via DAHUA recorder
Main features:	• D-WDR - Wide Dynamic Range • 2D-DNR - Digital Noise Reduction • Day/night mode • Auto White Balance • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance

Power supply:	12 V DC / 340 mA
Power consumption:	≤ 4.1 W
Housing:	Dome, Metal
Color:	White
"Index of Protection":	IP67
Vandal-proof:	IK10
Operation temp:	-40 °C ... 60 °C
Weight:	0.4 kg
Dimensions:	Ø 122 x 89 mm
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

PRESENTATION

Camera is out from clamping ring:



Mounting side view:



In the kit:



OUR TESTS

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

