

Code: APTI-27C61-2812WP

IP CAMERA **APTI-27C61-2812WP** - 1080p 2.8 ... 12 mm

Net: **102.28 EUR** Gross: **102.28 EUR**

IP camera with efficient H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 1080p.

Camera bracket allows to adjust the camera to any direction, and power cables are hidden inside the bracket.

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.



SPECIFICATION

Standard:	TCP/IP
Sensor:	1/2.8 " Sony CMOS IMX322
Digital Image Processor:	AMBARELLA S2L
Matrix size:	2.4 Mpx
Resolution:	1920 x 1080 - 1080p
Lens:	2.8 ... 12 mm, 3 Mpx
View angle:	82 ° ... 25 ° (manufacturer data) 91 ° ... 36 ° (our tests result)
S/N ratio:	> 50 dB
Range of IR illumination:	60 m (manufacturer data) 40 m (our tests result)
IR illuminator power adjustment:	Automatic
Image compression method:	H.264
Alarm inputs / outputs:	—
Bitrate:	64 ... 12000 kbps
Main stream frame rate:	max. 25 fps - 1080p
Audio:	—
Network interface:	10/100 Base-T (RJ-45)
Default IP address:	192.168.1.168
Default admin user / password:	admin / admin
Network protocols:	RTSP, PPPOE, DHCP, DDNS, NTP, UPnP, TCP

Web browser access ports:	80
PC client access ports:	80
WEB Server:	Built-in
Mobile client access ports:	80
Max. number of on-line users:	10
Port ONVIF:	80
ONVIF:	2.4
RTSP URL:	rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream
Mobile phones support:	Port no.: 80 or access by a cloud (P2P) • Android: Free application FREEIP • iOS (iPhone): Free application FREEIP
RS-485 interface:	—
Main features:	• ICR - Movable InfraRed filter • ISO+ - improve image quality when working at night conditions with active IR illuminator • 3D-DNR - Digital Noise Reduction • WDR - Wide Dynamic Range • Motion Detection • Privacy zones • Configurable: brightness, contrast, saturation • Sharpness - sharper image outlines • Mirror - Mirror image • Day/night mode
Power supply:	• PoE (802.3af), • 12 V DC / 500 mA
Power consumption:	≤ 6 W
Housing:	Compact, Metal
Color:	White
"Index of Protection":	IP66
Operation temp:	-20 °C ... 60 °C
Weight:	1.00 kg
Dimensions:	290 x 100 x 95 mm
Supported languages:	English, Bulgarian, Chinese, French, Hebrew, Spanish, Dutch, Japanese, Korean, German, Persian, Polish, Portuguese, Italian, Turkish, Russian
Manufacturer / Brand:	APTi
Guarantee:	2 years

PRESENTATION



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60




Side view:



Bottom view:



Bracket dimensions:



In the kit:



OUR TESTS

Camera image at artificial illumination (about 30Lux):




Camera image at night conditions with internal built-in IR illuminator on:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Camera image at direct strong light opposite to camera:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

