

Code: GT-CI21C2-28ZW

IP CAMERA **GT-CI21C2-28ZW** - 1080p, 2.8 ... 8 mm - MOTOZOOM GEMINI TECHNOLOGY

Net: **64.78 EUR** Gross: **64.78 EUR**

IP camera with efficient H.264 / H.265 image compression algorithm for clear and smooth video streaming at maximal resolution of 1080p.

The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance). PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.



SPECIFICATION

Standard:	TCP/IP
Sensor:	1/2.8 " Sony CMOS
Digital Image Processor:	Hisilicon 3516C
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p , 1280 x 1024 - 1.4 Mpx , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p , 720 x 576 - D1
Lens:	2.8 ... 8 mm - Motozoom
View angle:	• 87 ° ... 37 ° (manufacturer data) • 98 ° ... 51 ° (our tests result)
S/N ratio:	> 50 dB
Range of IR illumination:	30 m
IR illuminator power adjustment:	Automatic
Image compression method:	H.265 / H.264 / MJPEG
Alarm inputs / outputs:	2 / 1
Bitrate:	16 ... 8000 kbps
Video output:	1 Vpp / 75 Ω
Main stream frame rate:	max. 25 fps - 2.1 Mpx
Network interface:	10/100 Base-T (RJ-45)

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Network protocols:	TCP/IP, UDP, HTTP, DHCP, RTSP, DDNS, NTP, PPPoE, UPnP, SMTP
Audio:	<ul style="list-style-type: none"> • External microphone input - RCA (CINCH) • Audio output - RCA (CINCH)
Mobile phones support:	Port no.: 5800 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application Fseye • iOS: Free application Fseye
Default IP address:	192.168.1.188
Default admin user / password:	admin / (null)
Web browser access ports:	80, 554, 1935
PC client access ports:	5050, 5051, 5052
WEB Server:	Built-in
Mobile client access ports:	5800
Max. number of on-line users:	10
Port ONVIF:	80
ONVIF:	2.21
RTSP URL:	rtsp://ip_address:554/ch01.264 - Main stream rtsp://ip_address:554/ch01_sub.264 - Sub stream
Memory card slot:	Micro SD memory cards up to 64GB support (possible local recording)
RS-485 interface:	✓
Main features:	<ul style="list-style-type: none"> • 3D-DNR - Digital Noise Reduction • WDR - 120 dB - Wide Dynamic Range • ICR - Movable InfraRed filter • CVBS, SPOT output • Possibility to change the resolution, quality and bit rate • Time mark and image description • Image rotation and mirror • Configurable: brightness, contrast, saturation • Sharpness - sharper image outlines • Day/Night mode - configurable • Possibility to add different privileges to the users • Privacy zones - max. 4 • RESET button • Intelligent image analysis : Target Count, Detection of item's reorientation in 3D space, Virtual Guard, area detection
Power supply:	<ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC / 290 mA
Power consumption:	≤ 3.5 W
Housing:	Compact, Metal
Color:	White
"Index of Protection":	IP66
Supported languages:	English, Polish
Operation temp:	-20 °C ... 60 °C
Weight:	0.646 kg
Dimensions:	Ø 71 x 188 mm
Manufacturer / Brand:	GEMINI TECHNOLOGY
Guarantee:	2 years

PRESENTATION

Front view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Side view:



At the bottom of the camera has an openable cover under which is hidden IR illuminator adjustment and extra video output:



Mounting dimensions:



In the kit:



Package:



OUR TESTS

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



Record from camera during daylight operation:

:

Record from camera during night conditions operation:

:

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------