

Code: APTI-AI508CA6-27135WP-Z

IP CAMERA **APTI-AI508CA6-27135WP-Z** - 5 Mpx 2.7 ... 13.5 mm - MOTOZOOM

Net: **108.27 EUR** Gross: **108.27 EUR**

IP camera with efficient H.265 / H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 5 Mpx.

Camera bracket allows to adjust the camera to any direction, and power cables are hidden inside the bracket. The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).

The used motozoom lens with 2.7 ... 13.5 mm focal length allows to remote view angle adjustment. PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.

The camera has extensive functions of intelligent image analysis.



SPECIFICATION

Standard:	TCP/IP
Matrix size:	5 Mpx
Sensor:	1/2.8 " SONY Starvis™ Back-illuminated CMOS
Resolution:	2592 x 1944 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens:	2.7 ... 13.5 mm - Motozoom
View angle:	103 ° ... 29 °
Range of IR illumination:	40 m
Image compression method:	H.265+ / H.265 / H.264+ / H.264
Main stream frame rate:	25 fps - 5 Mpx
Network interface:	10/100 Base-T (RJ-45)
Alarm inputs / outputs:	—
Audio:	• External microphone input - Jack 3.5 mm socket • Audio output - Jack 3.5 mm socket • Bi-directional audio streaming support • Audio transmission via network • Compliance with the AAC standard
WEB Server:	Built-in
Max. number of on-line users:	10

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

ONVIF:	19.12
RS-485 interface:	—
Memory card slot:	Micro SD memory cards up to 512GB support (possible local recording) (manufacturer data)
Mobile phones support:	Port no.: 80 or access by a cloud (P2P) • Android: Free application BitVision • iOS (iPhone): Free application BitVision
Default IP address:	192.168.1.168
Default admin user / password:	admin / admin
Web browser access ports:	80
PC client access ports:	80
Mobile client access ports:	80
Port ONVIF:	80
RTSP URL:	rtsp://user:password@ip_address:80/0 - Main stream rtsp://user:password@ip_address:80/1 - Sub stream
Main features:	• WDR - Wide Dynamic Range • 3D-DNR - Digital Noise Reduction • Anti-Flicker - The technology eliminates the tiring eyes flickering image effect • ROI - improve the quality of selected parts of image • BLC - Back Light Compensation • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • Day/Night mode - configurable • Privacy zones • Mirror - Mirror image • Sharpness - sharper image outlines • Intelligent image analysis : intrusion, crossing the line (tripwire), detection of people gathering, loitering detection, motion detection based on human detection
Power supply:	• PoE (802.3af), • 12 V DC / 850 mA
Power consumption:	≤ 10.2 W
Housing:	Compact - Metal
Color:	White
"Index of Protection":	IP67
Operation temp:	-20 °C ... 60 °C
Weight:	1 kg
Dimensions:	270 x 90 x 90 mm
Supported languages:	Polish, English, Bulgarian, Czech, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Italian
Manufacturer / Brand:	APTI
Guarantee:	2 years

PRESENTATION

Front view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60




Side view:



Bottom view:



Mounting side view:



Camera connectors:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

