

Code: DINB-13830

BUFFERED SWITCHING POWER SUPPLY ADAPTER **DINB-13830**

Net: **37.26 EUR** Gross: **37.26 EUR**

The buffered power supply adapter is designed to powering control panels, sensors, code locks, cameras, consoles, intercoms and other alarm system equipment.

DINB-13830 is designed to mount on the DIN 35 mm rail.




SPECIFICATION

Adapter type:	Switching
Input voltage:	90 ... 264 V AC
Output voltage:	• 11 ... 13.8 V DC (buffer operation) • 9 ... 13.8 V DC (battery mode)
Max. output current (total):	3.5 A
Battery charging current:	0.5 A
Power:	48 W (max)
Protections:	• Short-circuit • Overvoltage • Overload • Reverse polarity connection • Discharge
Adapter operation control:	• AC input voltage presence indication • DC output voltage presence indication • Battery charging indication
Housing type:	Plastic, DIN, TS-35 rail mounting
Weight:	0.36 kg
Dimensions:	122 x 93 x 50 mm
Manufacturer / Brand:	PULSAR
Guarantee:	2 years

PRESENTATION

Adapter connectors:


DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Mounting side view:



Dimensions:



PACKAGE

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

