

Code: BCS-EA25FSR3(H2)

AHD, HD-CVI, HD-TVI CAMERA **BCS-EA25FSR3(H2)** - 5 Mpx 2.8 mm

Net: **46.15 EUR** Gross: **46.15 EUR**

Megapixel camera with 1/2.8" CMOS sensor and AHD / HD-CVI / HD-TVI.

The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in max. 8 Mpx (4K UHD) resolution. During transmission there are no delays and is maintained the original, high quality image. In the case of video transmission using a twisted pair cable and matching transformers (balun), be aware of the possibility of signal reflections and interfering signals.



SPECIFICATION

Standard:	AHD / HD-CVI / HD-TVI / CVBS
Resolution:	2704 x 1950 - 5 Mpx @ AHD / HD-TVI @ 20 fps , 2560 x 1440 - 3.7 Mpx @ AHD / HD-CVI / HD-TVI @ 25 fps 1920 x 1080 - 1080p - AHD, HD-TVI, HD-CVI @ 25 fps
Sensor:	1/2.8 " Progressive Scan CMOS
Lens:	2.8 mm, F1.2
View angle:	103 °
Range of IR illumination:	30 m
S/N ratio:	> 50 dB
Video output:	AHD / HD-CVI / HD-TVI, 1 Vpp / 75 Ω
OSD menu:	✓
Audio:	• Microphone built-in • Audio output
Main features:	• D-WDR - Wide Dynamic Range • BLC - configurable Back Light Compensation • 3D-DNR - Digital Noise Reduction • HLC - High Light Compensation (spot) • ICR - Movable InfraRed filter • AGC - Automatic Gain Control • Auto White Balance
Power supply:	12 V DC / 420 mA
Power consumption:	< 5 W
Housing:	Dome, Metal
Color:	White

"Index of Protection":	IP66
Mechanical protection class:	—
Operation temp:	-20 °C ... 60 °C
Weight:	0.3 kg
Dimensions:	Ø 94 x 80 mm
Manufacturer / Brand:	BCS
Guarantee:	3 years

PRESENTATION


Camera is out from clamping ring:



Dimensions:



Configuration switches:



Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------