

Code: DS-KD8002-VM

VIDEO DOORPHONE **DS-KD8002-VM** Hikvision

Net: 6 171.79 NOK Gross: 6 171.79 NOK

Video Doorphone is mounted in a flush-mounted housing.
The product has been equipped with a network interface, so it can be combined with systems based on the **iVMS-4200** software.



SPECIFICATION

Sensor:	1.3 Mpx CMOS
Display:	3.5 " TFT LCD, 480 x 320 px
Image compression method:	H.264
LED illuminator:	✓
IR illuminator:	—
Compatibility:	Hikvision IP Video Doorphones
RS-485:	✓
Ethernet:	10/100/1000 Base-TX
UTP category:	UTP cat. 5e
Door opening sensor:	4 pcs



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Main features:	<ul style="list-style-type: none"> • 13.56 MHz S50 proximity reader built-in, 2500 indexed users, • Wiegand interface, • Keyboard built-in, • LCD display, • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Tamper detection - removing from mounting surface, • Tamper protections, • Alarm inputs / outputs : 4 / 2, • Ability to work with reed switch and signalling the door being opened too long • Auto-uploads alarm messages to Master station or once the duress code is entered to open the door, • Auto-uploads captured pictures to FTP or the client, • Port USB 2.0, • Configuration possibility from PC - iVMS-4200 application • Default administrator password : 123456
Operation temp:	-40 °C ... 70 °C
Power supply:	12 V DC / 1.25 A
Power consumption:	≤ 15 W
Housing:	Aluminum
Color:	Silver / Black
Weight:	2.6 kg
Dimensions:	418 x 145 x 61 mm
Supported languages:	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Russian
Manufacturer / Brand:	Hikvision
SAP Code:	305300152
Guarantee:	3 years

PRESENTATION

Front panel:



Rear view:





DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60




View after remove the cover:



Connectors view:



Example of application:



1. UTP cat. 5e/6
2. Fiber optic
3. Single resident
4. Single resident panels
5. Resident 2 panel
6. Resident 3 panel

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

7. Resident 4 panel
 8. Switch dedicated to the HIKVISION video intercom systems
 9. Switch
 10. Client software
 11. System management center
 12. System management from guarding room
 13. IP Camera
 14. DS-KD8002-VM
 15. Reader with keypad
- In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------