

Code: DS-KB8112-IM

VIDEO DOORPHONE **DS-KB8112-IM** Hikvision

Net: **163.78 EUR** Gross: **163.78 EUR**

The device cooperates with video doorphones, and other panels working in Hikvision IP standard.



SPECIFICATION

Sensor:	1/3 " CMOS, 720p
LED illuminator:	—
IR illuminator:	✓ 940 nm (invisible to the human eye), Range : 5 m
Compatibility:	Hikvision IP Video Doorphones
proximity reader built-in:	—
UTP category:	UTP cat. 5e
Alarm inputs:	1 pcs
Relay outputs:	1 pcs NO/NC
RS-485:	—
Ethernet:	1 x RJ-45 - 10/100 Base-T
Main features:	• D-WDR - Wide Dynamic Range, • Motion Detection , • Configurable: brightness, contrast, saturation • Microphone built-in, • Speakers built-in, • Bidirectional communication, • The device has the ability to work with the Hik-Connect application for mobile devices, without the use of an internal panel
Operation temp:	-30 °C ... 50 °C
Power supply:	• PoE (802.3af), • 12 V DC / 1 A

Housing:	Metal, Waterproof, Vandal-proof - IK09
"Index of Protection":	IP66
Color:	Black
Weight:	0.79 kg
Dimensions:	162 x 74 x 54 mm
Supported languages:	English
Manufacturer / Brand:	Hikvision
SAP Code:	305300432
Guarantee:	3 years

PRESENTATION

Particular elements:



Device connectors:



Connectors description:



Rear view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------