

Code: BAT-RECHARGE/VC2SL

CHARGER BAT-RECHARGE/VC2SL XTAR

Net: 18.10 EUR Gross: 18.10 EUR

The BAT-RECHARGE/VC2SL Charger is the versatile device for many types of batteries.

Supports protected PCM/PCB batteries in sizes 20700/21700. The LCD display informs about the charging capacity, cell voltage, charging current and internal resistance of the cell.

Attention! Power adapter not included in the kit.



SPECIFICATION

Battery type:	- Li-Ion 3.6 / 3.7 V - ICR / IMR / INR : 10440, 14500, 14650, 16340, 16650, 17335, 17500, 17670, 18350, 18490, 18500, 18505, 18650, 18700, 20700, 21700, 22650, 25500, 26650, - Ni-MH, Ni-Cd 1.2 V - AAAA / AAA / AA / A / C
Battery charging current:	0.5 A @ 2 pcs , 1 A @ 2 pcs , 2 A @ 1 pcs
LED indicator:	—
LCD display:	✓
Main features:	- The LCD display informs about the charging capacity, cell voltage, charging current and internal resistance of the cell, - Supports protected PCM/PCB batteries in sizes 20700/21700, - Deeply discharged cell reactivation function, - Power Bank (5V, max. 1A) function - Charging Li-ion batteries controlled by a three-stage processor TC/CC/CV charging process - charging Ni-MH batteries with the CC method 2 independent charging channels - End of charge voltage : 4.2 V @ Li-Ion, 1.45 V @ NiMH - Short-circuit protection - Protection against reverse polarity connection - Thermal protection - USB-C / USB-A cable included
Power supply:	5 V DC / 2 A @ USB-C socket (power adapter not included)
Weight:	0.11 kg
Dimensions:	68 x 137 x 34 mm 80 cm (cable length)
Manufacturer / Brand:	XTAR
Guarantee:	2 years

PRESENTATION



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Top view:





Example of displayed information:



In the kit:



OUR OPINIONS



- It gives fast, safe batteries charging.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

