

Code: UT-522

GROUNDING RESISTANCE METER **UT-522** UNI-T

Net: **198.30 EUR** Gross: **198.30 EUR**

The UT-522 meter allows to measure: grounding resistance of power installations, grounding resistance of devices, resistance of lightning protection systems, etc. The design of the device allows for a complete, accurate measurement of the grounding resistance using 3 leads and a simple, approximate measurement using 2 leads.



SPECIFICATION

Resistance measurement:	40 $\Omega \pm (2\% + 20)$ @ 0.01 Ω , 400 $\Omega \pm (2\% + 3)$ @ 0.1 Ω , 4000 $\Omega \pm (2\% + 3)$ @ 1 Ω • Auxiliary resistance : 500 $\Omega \pm 5\%$ • Measuring voltage : ≤ 10 V AC @ ~820 Hz
Ground voltage measurement:	400 V $\pm (1.0\% + 6)$ @ 1 V
Automatic change of measuring ranges:	—
RS-232:	—
USB:	—
Main features:	• Hold - stopping the meter reading, • The measurement can be performed in full or simplified configuration, • Warning of poor connection of leads during measurement, • Large, readable LCD display with backlight, • Low battery level alarm, • Aesthetic and solid construction, • The set includes a practical case
Operation temp:	5 $^{\circ}\text{C}$... 40 $^{\circ}\text{C}$
Permissible relative humidity:	$\leq 80\%$ (non-condensing)
Power supply:	6 x 1.5V, type AA/LR6/FR6 battery - included
Weight:	0.42 kg
Dimensions:	160 x 100 x 70 mm
Manufacturer / Brand:	UNI-T
Guarantee:	2 years

PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Front panel:



Front panel cover:



Rear view:



Place for batteries 6 x 1.5V AA:



In the kit:



Device is secured by handy case:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

