

Code: UT-593

MULTIFUNCTION METER FOR ELECTRICAL INSTALLATIONS UT-593 UNI-T

Net: 467.73 EUR Gross: 467.73 EUR

The UT-593 is a multifunction meter for measurements in electrical installations, dedicated to electricians. The device is also a comprehensive tester for the safety of electrical installations. The UT-593 allows you to measure insulation resistance, short circuit loop impedance with/without RCD tripping, line impedance, continuity of protective and equalizing conductors, test of trip current and RCD tripping time, AC voltage value, and the phase sequence display.

Attention! High voltage is required to correctly measure the insulation resistance value. During the measurement one should be particularly careful and strictly follow the recommendations included in the device manual.



SPECIFICATION

Resistance measurement:	• Test voltage 250 V : 0.05 MΩ ... 250 MΩ • Test voltage 500 V : 0.05 MΩ ... 500 MΩ • Test voltage 1000 V : 0.05 MΩ ... 1000 MΩ
Measuring accuracy:	0.05 M Ω ... 1000 M Ω $\pm$ (5% + 5)
Open circuit voltage:	Test voltage $\pm$ 10 %
Test current:	0.9 mA ... 1.1 mA
Short-circuit current:	< 1.8 mA
AC voltage measurement:	0 V ... 440 V $\pm$ (2% + 3) @ 1 V
DC voltage measurement:	0 V ... $\pm$ 440 V $\pm$ (2% + 3) @ 1 V
Measurement of small resistances:	0.01 Ω ... 200 Ω $\pm$ (2% + 5)
Frequency measurement:	20 Hz ... 100 Hz - for reference only
Test of RCDs:	• Working voltage: 220V $\pm$ 10 % • Test current: 10mA / 30mA / 100mA / 300mA / 500mA • Switch-off time ranges : - 0 ... 2000 ms $\pm$ (5% + 5) @ 1/2 x nominal value of the residual current - 0 ... 500 ms $\pm$ (5% + 5) @ 1 x nominal value of the residual current, Selective RCD - 0 ... 300 ms $\pm$ (5% + 5) @ 1 x nominal value of the residual current - 0 ... 40 ms $\pm$ (5% + 5) @ 5 x nominal value of the residual current
RCD tripping current measurement:	Increasing current test: 10 mA / 30 mA / 100 mA / 300 mA / 500 mA $\pm$ 10 %
RCD automatic test:	✓

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Phase sequence test:	100 V ... 440 V / 45 Hz ... 65 Hz
Continuity measurement of protective and equalizing conductors:	0 Ω ... 199 $\Omega \pm (2\% + 5)$ Measuring current > 20 mA @ 0 ... 2 Ω
Line impedance measurement (L-N):	• 0.05 Ω ... 1.99 $\Omega \pm (5\% + 5)$ • 2 Ω ... 19.99 $\Omega \pm (5\% + 5)$ • 20 Ω ... 2000 $\Omega \pm (5\% + 5)$ Measuring current : 20 A / 20 ms Measuring range of prospective short-circuit current : 0 ... 26 kA
Short circuit loop impedance measurement (L-PE):	• 0.05 Ω ... 1.99 $\Omega \pm (5\% + 5)$ • 2 Ω ... 19.99 $\Omega \pm (5\% + 5)$ • 20 Ω ... 2000 $\Omega \pm (5\% + 5)$ Measuring current : 20 A / 20 ms Measuring range of prospective short-circuit current : 0 ... 26 kA
Automatic change of measuring ranges:	✓
RS-232:	—
USB:	—
Main features:	• Warning of using high voltage during the measurement, • Phase switch 0° / 180° during RCD test, • Automatic identification of AC/DC voltage, • Reset function for measuring low resistances, • Large, readable LCD display with backlight, • Buzzer, • Automatic power-off, • Low battery indicator, • Aesthetic and solid construction
Operation temp:	0 °C ... 40 °C
Permissible relative humidity:	≤ 85 % (non-condensing)
Power supply:	8 x 1.5V, type AA/LR6/FR6 battery - included
Weight:	1.1 kg
Dimensions:	210 x 175 x 90 mm
Manufacturer / Brand:	UNI-T
Guarantee:	2 years

PRESENTATION

Front panel:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Top view:




Rear view:



Place for batteries 8 x 1.5V AA:



In the kit:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60