

Code: TL-MERC-MW302R

ROUTER **TL-MERC-MW302R** 2.4 GHz 300 Mbps TP-LINK / MERCUSYS

Net: **14.22 EUR** Gross: **14.22 EUR**

The TL-MERC-MW302R is a wideband router (for cable modem) and 2-port FastEthernet switch.

Main applications include Internet accesses in small and medium size businesses, SOHO, and homes.

The TL-MERC-MW302R ensures advanced access control, and its DHCP server supports static assignment of IP addresses. The device also supports virtual servers, DMZ zone, remote logging and management.



SPECIFICATION

Frequency range:	2.4 GHz ... 2.4835 GHz
Antenna type:	2 x Omnidirectional antenna 5 dBi
Standards:	IEEE 802.11 b/g/n
Baud rates:	300 Mbps
LAN ports:	• 1 x 10/100 Mbps - WAN, • 2 x 10/100 Mbps - LAN
LED indicators:	Power / WLAN / WAN / LAN
Receiver sensitivity:	• 270M : -73 dBm @ 10% PER • 130M : -75 dBm @ 10% PER • 54M : -77 dBm @ 10% PER • 11M : -90 dBm @ 10% PER • 6M : -94 dBm @ 10% PER • 1M : -96 dBm @ 10% PER
Transmitter power:	< 20 dBm
DDNS:	No-IP, DynDNS
DHCP server:	✓
Firmware update:	✓
Operation modes:	Router, Range Extender, Access Point, WISP
Protections:	• WPA-PSK/WPA2-PSK • IP-MAC Binding
Management interface:	Web browser

Main features:	• RESET button • Built-in 2-port switch • Guest Network - a separate and secure network for guests • Remote management • Firewall • parental control • Access control • Static / dynamic routing • WAN : PPPoE, PPTP, L2TP • Port forwarding : Virtual Server, UPnP, DMZ • DHCP server • IPv6 compliance
Power supply:	5 V DC / 0.6 A (power adapter included)
Operation temp:	0 °C ... 40 °C
Permissible relative humidity:	10 % ... 90 % (non-condensing)
Weight:	0.11 kg
Dimensions:	114 x 94 x 26 mm
Manufacturer / Brand:	TP-LINK / MERCUSYS
Guarantee:	2 years

PRESENTATION



Device connectors:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60