

Code: CUDY-M1800

ACCESS POINT **CUDY-M1800** Wi-Fi 6, 2.4 GHz, 5 GHz, 574 Mbps + 1201 Mbps

Net: **71.02 EUR** Gross: **71.02 EUR**

The CUDY-M1800 access point broadcasts 2 separate wireless networks in the 5 GHz band with speed 1201 Mb/s and in the 2.4 GHz band with speed 574 Mb/s. Simple tasks such as sending e-mails or web browsing can be handled by the 2.4 GHz band while bandwidth intensive tasks like online gaming or HD video streaming can be processed by the 5 GHz band - all at the same time.

Main applications include Internet accesses in small and medium size businesses, SOHO, and homes. Thanks to the advanced Whole Home Mesh technology, devices are automatically switched when moving around the house.

Supports 802.11ax standard - the next generation of Wi-Fi. The high performance of the Wi-Fi 6 ensures more connected devices and faster speeds.



SPECIFICATION

Frequency range:	2.4 GHz, 5 GHz ,
Antenna type:	4 x Omnidirectional antenna - embedded
Standards:	IEEE 802.11ax/n/b/g @ 2.4 GHz , IEEE 802.11ax/ac/n/a @ 5 GHz
Baud rates:	574 Mbps + 1201 Mbps
LAN ports:	1 x 10/100/1000 Mbps - WAN 1 x 10/100/1000 Mbps - LAN
LED indicators:	Power / System, Link/Act
DDNS:	✓
DHCP server:	✓
Firmware update:	✓
Protections:	WEP, WPA/WPA2, WPA-PSK/WPA2-PSK, WPA3
Management interface:	Web browser
Operation modes:	• Router, • AP, • Range Extender, • WISP
Transmitter power:	< 20 dBm @ 2.4 GHz < 23 dBm @ 5 GHz

Power supply:	12 V DC / 1.5 A (power adapter included)
Main features:	• Support for CUDY Whole Home Mesh technology • Wi-Fi 6 support - a standard that offers higher speeds, better performance in high-traffic environments • Beamforming (TxBF) - technology that allows to create a beam of radio waves in order to improve the quality of connection with client devices located further away from the signal source • MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network • Pairing button • RESET button • WMM (Wi-Fi Multimedia) • WAN : Fixed, or dynamic IP address, PPPoE • DHCP : DHCP server, DHCP client list, address reservation • Guest Network - a separate and secure network for guests • NAT : Port forwarding, Port Triggering, UPnP, DMZ • VPN networks: PPTP, L2TP, OpenVPN, WireGuard, IPSec, Zerotier • Access control • parental control • Remote management • VLAN • IPTV compliance • IPv6 compliance • Supports max. 100 devices • Indoor coverage area : 185 m²
Operation temp:	0 °C ... 40 °C
Permissible relative humidity:	max. 85 % (non-condensing)
Weight:	0.42 kg
Dimensions:	Ø 110 x 155 mm
Manufacturer / Brand:	CUDY
Guarantee:	2 years

PRESENTATION



Rear view:

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Device connectors:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------