

Code: RUT241

# ACCESS POINT 4G LTE +ROUTER **RUT241** 2.4 GHz 300 Mbps Teltonika

Net: **149.34 EUR** Gross: **149.34 EUR**

The RUT241 Wireless Router, operating in accordance with the 802.11 b/g/n standard, allows to share a network connection between several users in areas that are covered by 3G/4G signal.

Main applications include Internet accesses in small and medium size businesses, SOHO, and homes.



## SPECIFICATION

Frequency range:	2.4 GHz
Antenna type:	1 x Omnidirectional antenna Wi-Fi - 5 dBi (SMA connector) , 2 x Omnidirectional antenna 4G LTE - 4 dBi (SMA-RP connector)
Standards:	IEEE 802.11 b/g/n, 4G LTE, 3G, 2G
Baud rates:	11n : 300 Mbps 11g : 54 Mbps 11b : 11 Mbps LTE : 150 / 42 / 0.234 Mbps (4G / 3G / 2G)
LAN ports:	<ul style="list-style-type: none"><li>• 1 x 10/100 Mbps - WAN</li><li>• 1 x 10/100 Mbps - LAN</li></ul>
Transmitter power:	≤ 20 dBm @ 2.4 GHz ≤ 23 dBm @ 4G LTE ≤ 24 dBm @ 3G WCDMA ≤ 33 dBm @ 2G GSM
LED indicators:	Power, WAN, WLAN, LAN, LTE (4G / 3G / 2G), Signal indicator
Network type:	4G, 3G, 2G
LTE:	✓
QSS:	—
WDS:	—
DHCP server:	✓

Protections:	<ul style="list-style-type: none"> <li>• WPA2-Enterprise - PEAP</li> <li>• WPA-PSK/WPA2-PSK</li> <li>• WPA-EAP</li> <li>• AES-CCMP</li> <li>• WEP</li> <li>• TKIP</li> <li>• Auto Cipher modes</li> <li>• Client separation</li> <li>• SSID hiding</li> <li>• MAC addresses filtering</li> </ul>
Management interface:	Web browser, Teltonika RMS application, SMS
Main features:	<ul style="list-style-type: none"> <li>• Support for IoT (Internet of Things) systems,</li> <li>• Ability to work as a Hotspot,</li> <li>• Support for VoIP technology,</li> <li>• SIM socket</li> <li>• DHCP Relay support</li> <li>• DHCP client list</li> <li>• Static / dynamic routing</li> <li>• VPN support</li> <li>• Default address : 192.168.1.1</li> <li>• Configuration using the Teltonika RMS application</li> <li>• WAN Connection Backup - thanks to the fully functional WAN / LAN port, you can use various types of backup connections, including cable, fiber and DSL modems</li> </ul>
Power supply:	<ul style="list-style-type: none"> <li>• 9 V DC / 1 A (power adapter included)</li> <li>• 9 ... 30 V DC</li> <li>• 9 ... 30 V DC - Passive PoE, Powering from LAN1</li> </ul>
Power consumption:	≤ 6.5 W
Operation temp:	-40 °C ... 75 °C
Permissible relative humidity:	10 % ... 90 % (non-condensing)
Weight:	0.13 kg
Dimensions:	83 x 80 x 25 mm
Manufacturer / Brand:	Teltonika
Guarantee:	2 years

## PRESENTATION

Connectors:





In the kit:



## PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------