

Code: TL-RE550

UNIVERSAL WI-FI RANGE EXTENDER **TL-RE550** 2.4 GHz, 5 GHz TP-LINK

Net: **75.75 EUR** Gross: **75.75 EUR**



The TL-RE550 device greatly extends existing wireless coverage in difficult-to-wire and "dead zones" places.

Thanks to the advanced OneMesh technology, devices are automatically switched when moving around the house. In addition, the device can also work as a wireless access point, increasing the functionality of the existing wired network by Wi-Fi connection.

SPECIFICATION

Frequency range:	2.4 GHz, 5 GHz
Antenna type:	3 x Omnidirectional antenna - Outdoor
Standards:	IEEE 802.11 a/b/g/n/ac
Baud rates:	• 600 Mbps @ 2.4 GHz • 1300 Mbps @ 5 GHz
Receiver sensitivity:	2.4 GHz : • 54 Mbps 11g : -77 dBm @ 10% PER • HT20 mcs7 11n : -73 dBm @ 10% PER • HT40 mcs7 11n : -70 dBm @ 10% PER 5 GHz : • 6 Mbps 11a : -93 dBm @ 10% PER • 54 Mbps 11a : -76 dBm @ 10% PER • HT20 mcs8 11ac : -68 dBm @ 10% PER • HT40 mcs9 Mbps 11ac : -64 dBm @ 10% PER • HT80 mcs9 Mbps 11ac : -61 dBm @ 10% PER
LED indicators:	5 GHz, 2.4 GHz, Power, Wi-Fi - Signal indicator
QSS:	—
Operation modes:	• Range Extender - signal amplifier • Access Point - Access Point mode
Protections:	64/128-bit WEP, WPA/WPA-PSK2
LAN ports:	1 x (RJ45) 10/100/1000 Mbps - Ethernet
Management interface:	Web browser, Tether application

Transmitter power:	• < 20 dBm @ 2.4 GHz • < 23 dBm @ 5 GHz
Main features:	• 2.4 GHz (450Mb/s) and 5 GHz (1300Mb/s) bands support • Intelligent LED indicator helps you find the best location for the device, which can achieve optimal network coverage • Wireless transmission statistics • Access control • Domain Login Function • Access Point - Built-in • WPS button • RESET button
Power supply PoE:	—
Power supply:	230 V AC
Power consumption:	≤ 16 W
Weight:	0.24 kg
Dimensions:	204 x 142 x 66 mm
Manufacturer / Brand:	TP-LINK
Guarantee:	3 years

PRESENTATION

Front view:



Rear view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Sides view:





Control keys:



Ethernet socket view:





PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------