	IP CAMERA APTI-86C6-27135WP-Z - 8.3 Mpx, 4K UHD 2.7 ... 13.5 mm - MOTOZOOM	IP CAMERA APTI-AI801CA4-27135Z 8.3 Mpx 2.7 ... 13.5 mm - MOTOZOOM	IP CAMERA APTI-AI802C6-27135W-Z - 8.3 Mpx 4K UHD 2.7 ... 13.5 mm - MOTOZOOM	IP CAMERA TC-C38TS SPEC:I8/A/E/Y/M/H/2.7-13.5MM/V4.0 - 8 Mpx 2.7 ... 13.5 mm TIANDY	IP VANDALPROOF CAMERA IPC2328SB-DZK-I0 - 8.3 Mpx 2.8 ... 12 mm - MOTOZOOM UNIVIEW
	157.50 EUR 157.50 EUR	171.64 EUR 171.64 EUR	110.48 EUR 110.48 EUR	580.83 EUR 580.83 EUR	610.26 EUR 610.26 EUR
Standard	IP	IP	TCP/IP	IP	TCP/IP
Matrix size	...	...	8.3 Mpx	...	8.3 Mpx
Sensor	1/2.8 " SONY Starvis™ Back-illuminated CMOS	1/2.8 " SONY Starvis™ Back-illuminated CMOS	1/2.8 " SONY Starvis™ Back-illuminated CMOS	1/2.8 " Progressive Scan CMOS	1/2.8 " Progressive Scan CMOS
Resolution	3840 x 2160 - 8.3 Mpx, 4K UHD , 3072 x 2048 - 6 Mpx , 2592 x 1536 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	3840 x 2160 8.3 Mpx , 3072 x 2048 - 6 Mpx , 2592 x 1536 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	3840 x 2160 - 8.3 Mpx 4K UHD , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	3840 x 2160 - 8 Mpx , 3072 x 2048 - 6 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	3840 x 2160 - 8.3 Mpx , 3072 x 1728 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p
Lens	2.7 ... 13.5 mm - Motozoom	2.7 ... 13.5 mm - Motozoom	2.7 ... 13.5 mm - Motozoom	2.7 ... 13.5 mm Motozoom	2.8 ... 12 mm - Motozoom, AutoFocus
White light LED illuminator range	...	...	...	...	...
View angle	• 96 ° ... 26 ° (manufacturer data) • 100 ° ... 32 (our tests result)	• 103 ° ... 29 ° (manufacturer data) • 100 ° ... 31 ° (our tests result)	103 ° ... 29 ° (manufacturer data)	106 ° ... 31 °	• 107 ° ... 29 ° (manufacturer data) • 100 ° ... 30 ° (our tests result)
Min. illumination	...	...	...	...	...
S/N ratio	...	...	...	...	> 52 dB
Compression	...	...	...	...	...
Range of IR illumination	60 m	40 m	60 m	80 m	50 m
Image compression method	H.265+ / H.265 / H.264+ / H.264	H.265+ / H.265 / H.264 / MJPEG	H.265+ / H.265 / H.264+ / H.264	S+265 / H.265 / H.264	Ultra 265 / H.265 / H.264 / MJPEG
Access from PC	...	...	...	Port no.: 3000 or access by a cloud (P2P) - PC: Free application Easy7 Smart Client Express	...
Interface	...	...	...	10/100 Base-TX (RJ-45)	...
Alarm inputs / outputs	1 / 1	1 / 1	—	2 / 1	1 / 1
Main stream frame rate	max. 20 fps - 8 Mpx max. 25 fps - 3.7 Mpx	25 fps @ 8.3 Mpx	20 fps - 8 Mpx	• 25 fps @ 8 Mpx	20 fps @ 8.3 Mpx 25 fps @ 5 Mpx
Network interface	10/100 Base-T (RJ-45)	10/100 Base-T (RJ-45)	10/100 Base-T (RJ-45)	...	10/100 Base-T (RJ-45)
Wiegand interface	...	...	...	...	...
Intelligent image analysis	• intrusion - classification of people and vehicles • crossing the line (tripwire) - classification of people and vehicles • loitering detection • detection of people gathering	• intrusion - classification of people and vehicles • crossing the line (tripwire) - classification of people and vehicles • detection of people gathering • loitering detection	...	• crossing the line (tripwire) • video tampering • detection of persons on duty • protective helmet detection • detection of people gathering • people counting • illegal parking • running • detection of loitering in a given area • heat map • abandoned/missing object • classification of people and vehicles • double crossing the line • intrusion	...
Protections	...	...	...	• Overvoltage protection : 2 kV • Protection against lightning discharges : 6 kV	...

	IP CAMERA IPC-HFW2841T-ZAS-27135 - 8.3 Mpx 4K UHD 2.7 ... 13.5 mm - MOTOZOOM DAHUA	IP CAMERA IPC-HFW2841T-ZAS-27135-BLACK - 8.3 Mpx 4K UHD 2.7 ... 13.5 mm - MOTOZOOM DAHUA	IP CAMERA IPC-HFW3549T1-ZAS-PV-27135 TiOC Full-Color - 5 Mpx 2.8 ... 13.5 mm - MOTOZOOM DAHUA	IP CAMERA IPC-HFW3842T-ZAS-2712 - 8.3 Mpx 4K UHD 2.7 ... 12 mm - MOTOZOOM DAHUA	IP CAMERA IPC-HFW3842T-ZAS-2712-BLACK - 8.3 Mpx 4K UHD 2.7 ... 12 mm - MOTOZOOM DAHUA
	460.89 EUR 460.89 EUR	460.89 EUR 460.89 EUR	574.14 EUR 574.14 EUR	652.98 EUR 652.98 EUR	652.98 EUR 652.98 EUR
Standard	TCP/IP	TCP/IP	TCP/IP	TCP/IP	TCP/IP
Matrix size	8.3 Mpx 4K UHD	8.3 Mpx 4K UHD	5 Mpx	8.3 Mpx 4K UHD	8.3 Mpx 4K UHD
Sensor	1/2.7 " Progressive Scan CMOS	1/2.7 " Progressive Scan CMOS	1/2.7 " Progressive Scan CMOS	1/1.8 " Progressive Scan CMOS	1/1.8 " Progressive Scan CMOS
Resolution	3840 x 2160 - 8.3 Mpx 4K UHD , 3072 x 2048 - 6 Mpx , 3072 x 1728 - 5 Mpx , 2880 x 1620 - 4.7 Mpx , 2688 x 1520 - 4 Mpx , 2048 x 1536 - 3 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p	3840 x 2160 - 8.3 Mpx 4K UHD , 3072 x 2048 - 6 Mpx , 3072 x 1728 - 5 Mpx , 2880 x 1620 - 4.7 Mpx , 2688 x 1520 - 4 Mpx , 2048 x 1536 - 3 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p	2960 x 1668 - 5 Mpx , 2880 x 1620 - 4.7 Mpx , 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2048 x 1536 - 3 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p	3840 x 2160 - 8.3 Mpx 4K UHD , 3072 x 2048 - 6 Mpx , 3072 x 1728 - 5 Mpx , 2592 x 1944 - 5 Mpx , 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2048 x 1536 - 3 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p	3840 x 2160 - 8.3 Mpx 4K UHD , 3072 x 2048 - 6 Mpx , 3072 x 1728 - 5 Mpx , 2592 x 1944 - 5 Mpx , 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2048 x 1536 - 3 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Lens	2.7 ... 13.5 mm - Motozoom	2.7 ... 13.5 mm - Motozoom	2.8 ... 13.5 mm - Motozoom	2.7 ... 12 mm - Motozoom	2.7 ... 12 mm - Motozoom
White light LED illuminator range	...	...	50 m	...	...
View angle	• 113 ° ... 31 ° (manufacturer data) • 110 ° ... 32 ° (our tests result)	• 113 ° ... 31 ° (manufacturer data) • 106 ° ... 32 ° (our tests result)	113 ° ... 36 ° (manufacturer data)	• 113 ° ... 47 ° (manufacturer data) • 104 ° ... 47 ° (our tests result)	• 113 ° ... 47 ° (manufacturer data) • 106 ° ... 47 ° (our tests result)
Min. illumination	...	...	0.003 Lux / F1.0 (color)	...	...
S/N ratio	...	...	> 56 dB	...	...
Compression	H.265+ / H.265 / H.264+ / H.264 / MJPEG	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Range of IR illumination	60 m	60 m	40 m	60 m	60 m
Image compression method	...	...	AI H.265 / H.265+ / AI H.264 / H.264+	...	...
Access from PC	...	...	...	...	...
Interface	...	...	...	...	...
Alarm inputs / outputs	1 / 1	1 / 1	1 / 1	1 / 1	1 / 1
Main stream frame rate	20 fps @ 8 Mpx 25 fps @ 4 Mpx	20 fps @ 8 Mpx 25 fps @ 4 Mpx	20 fps @ 5 Mpx 25 fps @ 4 Mpx	25 fps @ 8 Mpx	25 fps @ 8 Mpx
Network interface	10/100 Base-T (RJ-45)	10/100 Base-T (RJ-45)	10/100 Base-T (RJ-45)	10/100 Base-T (RJ-45)	10/100 Base-T (RJ-45)
Wiegand interface	...	...	...	...	...
Intelligent image analysis	...	...	...	...	...

	IP CAMERA IPC-HFW3849T1-ZAS-PV TiOC Full-Color - 8.3 Mpx 4K UHD 2.8 ... 13.5 mm - MOTOZOOM DAHUA	IP VANDALPROOF CAMERA IPC-HFW5842E-ZE-0832-S3 WizMind S - 8.3 Mpx 4K UHD 8 ... 32 mm DAHUA	IP VANDALPROOF CAMERA IPC-HFW5842E-ZE-2712-S3 WizMind - 8.3 Mpx 4K UHD, 2.7 ... 12 mm - MOTOZOOM DAHUA	IP VANDALPROOF CAMERA IPC-HFW5842E-ZHE-2712-S3 WizMind S - 8.3 Mpx 4K UHD 2.7 ... 12 mm DAHUA	IP CAMERA DS-2CD1663G2-LIZU(2.8-12MM) ColorVu - 6 Mpx - MOTOZOOM Hikvision
	669.95 EUR 669.95 EUR	1042.19 EUR 1042.19 EUR	861.33 EUR 861.33 EUR	930.38 EUR 930.38 EUR	317.05 EUR 317.05 EUR
Standard	TCP/IP	IP	TCP/IP	IP	IP
Matrix size	8.3 Mpx	...	8.3 Mpx 4K UHD	...	...
Sensor	1/2.8 " Progressive Scan CMOS	1/1.8 " Progressive Scan CMOS	1/1.8 " Progressive Scan CMOS	1/1.8 " Progressive Scan CMOS	1/2.4 " Progressive Scan CMOS
Resolution	3840 x 2160 - 8.3 Mpx 4K UHD , 3072 x 2048 - 6 Mpx , 3072 x 1728 - 5 Mpx , 2592 x 1944 - 5 Mpx , 2688 x 1520 - 4 Mpx , 2048 x 1536 - 3 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p	3840 x 2160 - 8.3 Mpx 4K UHD , 3072 x 2048 - 6 Mpx , 3072 x 1728 - 5 Mpx , 2592 x 1944 - 5 Mpx , 2688 x 1520 - 4 Mpx , 2048 x 1536 - 3 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p	3840 x 2160 - 8.3 Mpx 4K UHD , 2592 x 1944 - 5 Mpx , 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p	3840 x 2160 - 8.3 Mpx 4K UHD , 3072 x 2048 - 6 Mpx , 3072 x 1728 - 5 Mpx , 2592 x 1944 - 5 Mpx , 2688 x 1520 - 4 Mpx , 2048 x 1536 - 3 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p 1280 x 960 - 1.3 Mpx 1280 x 720 - 720p	3200 x 1800 - 6 Mpx , 2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p
Lens	2.8 ... 13.5 mm - Motozoom	8 ... 32 mm	2.7 ... 12 mm - Motozoom	2.7 ... 12 mm - Motozoom	2.8 ... 12 mm - Motozoom
White light LED illuminator range	40 m	...	...	...	50 m
View angle	108 ° ... 34 °	42 ° ... 15 °	• 113 ° ... 47 ° (manufacturer data) • 104 ° ... 46 ° (our tests result)	113 ° ... 47 °	106 ° ... 36 °
Min. illumination	0.004 Lux / F1.0 (color)	...	...	...	...
S/N ratio	> 56 dB	...	...	...	...
Compression	...	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG / AI Coding	...	...
Range of IR illumination	50 m	120 m	60 m	60 m	50 m
Image compression method	AI H.265 / H.265+ / H.265 / AI H.264 / H.264+ / H.264	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...	Smart H.265+ / AI H.265 / H.265 / Smart H.264+ / AI H.264 / H.264 / H.264H / H.264B / MJPEG	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Access from PC	...	...	...	...	...
Interface	...	10/100 Base-T (RJ-45)	...	10/100 Base-T (RJ-45)	10/100 Base-T (RJ-45)
Alarm inputs / outputs	1 / 1	2 / 1	2 / 1	2 / 1	—
Main stream frame rate	25 fps @ 8 Mpx	25 fps @ 8.3 Mpx	25 fps @ 8.3 Mpx	25 fps @ 8.3 Mpx	20 fps @ 6 Mpx
Network interface	10/100 Base-T (RJ-45)	...	10/100 Base-T (RJ-45)	...	...
Wiegand interface	...	...	...	...	...
Intelligent image analysis	...	• crossing the line (tripwire) - classification of people and vehicles • intrusion - classification of people and vehicles • fast moving • scene changing • abandoned/missing object • parking detection • loitering detection • detection of people gathering • face detection - supports 6 types of facial attributes extraction • people counting - detection and maintenance of 4 independent areas	...	• crossing the line (tripwire) - classification of people and vehicles • intrusion - classification of people and vehicles • fast moving • scene changing • abandoned/missing object • parking detection • loitering detection • detection of people gathering • face detection - supports 6 types of facial attributes extraction • people counting - detection and maintenance of 4 independent areas	...

	IP VANDALPROOF CAMERA DS-2CD2663G2-IZS(2.8-12MM) ACUSENSE - 5.7 Mpx Hikvision	IP VANDALPROOF CAMERA DS-2CD2666G2-IZS(2.8-12MM)(C) - 6 Mpx Hikvision	IP VANDALPROOF CAMERA DS-2CD2683G2-IZS(2.8-12MM) ACUSENSE - 8.3 Mpx 4K UHD Hikvision	IP VANDALPROOF CAMERA DS-2CD2686G2-IZS(2.8-12MM)(C) ACUSENSE - 8.3 Mpx, 4K UHD - MOTOZOOM Hikvision	IP VANDALPROOF CAMERA DS-2CD2686G2-IZS(2.8-12MM)(C)/BLACK ACUSENSE - 8.3 Mpx, 4K UHD - MOTOZOOM Hikvision
	472.60 EUR 472.60 EUR	537.82 EUR 537.82 EUR	616.43 EUR 616.43 EUR	639.13 EUR 639.13 EUR	670.90 EUR 670.90 EUR
Standard	TCP/IP	TCP/IP	TCP/IP	TCP/IP	TCP/IP
Matrix size	6 Mpx	6.3 Mpx	8.3 Mpx	8.3 Mpx 4K UHD	8.3 Mpx 4K UHD
Sensor	1/2.4 " Progressive Scan CMOS	1/2.4 " Progressive Scan CMOS	1/2.8 " Progressive Scan CMOS	1/1.8 " Progressive Scan CMOS	1/1.8 " Progressive Scan CMOS
Resolution	3200 x 1800 - 5.7 Mpx , 2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p , 1280 x 720 720p	3200 x 1800 - 6 Mpx , 2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	3840 x 2160 - 8.3 Mpx 4K UHD , 3200 x 1800 - 5.7 Mpx , 2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p , 1280 x 720 720p	3840 x 2160 - 8.3 Mpx, 4K UHD , 3200 x 1800 - 5.7 Mpx , 2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p	3840 x 2160 - 8.3 Mpx, 4K UHD , 3200 x 1800 - 5.7 Mpx , 2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p
Lens	2.8 ... 12 mm - Motozoom	2.8 ... 12 mm - Motozoom	2.8 ... 12 mm - Motozoom	2.8 ... 12 mm - Motozoom	2.8 ... 12 mm - Motozoom
White light LED illuminator range	...	...	...	...	...
View angle	• 106 ° ... 35 °	• 99 ° ... 35 ° (manufacturer data) • 97 ° ... 35 ° (our tests result)	• 108 ° ... 30 °	• 108 ° ... 46 ° (manufacturer data) • 102 ° ... 46 ° (our tests result)	108 ° ... 46 °
Min. illumination	...	...	...	...	...
S/N ratio	...	...	...	...	...
Compression	H.265+ / H.265 / H.264+ / H.264 / MJPEG	H.265+ / H.265 / H.264+ / H.264 / MJPEG	H.265 / H.265+ / H.264 / H.264+ / MJPEG	H.265+ / H.265 / H.264+ / H.264 / MJPEG	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Range of IR illumination	60 m	60 m	60 m	60 m	60 m
Image compression method	...	...	...	...	...
Access from PC	...	...	...	...	...
Interface	...	...	...	...	...
Alarm inputs / outputs	1 / 1	1 / 1	1 / 1	1 / 1	1 / 1
Main stream frame rate	25 fps @ 6 Mpx	25 fps - 6.3 Mpx	25 fps @ 8.3 Mpx	25 fps - 8.3 Mpx	25 fps - 8.3 Mpx
Network interface	10/100 Base-T (RJ-45)	10/100 Base-T (RJ-45)	10/100 Base-T (RJ-45)	10/100 Base-T (RJ-45)	10/100 Base-T (RJ-45)
Wiegand interface	...	...	...	...	...
Intelligent image analysis	...	...	...	...	...

	IP VANDALPROOF CAMERA DS-2CD2686G2-IZSU/SL(2.8-12MM)(C) - 8.3 Mpx - MOTOZOOM Hikvision	IP VANDALPROOF CAMERA DS-2CD2687G2HT-LIZS(2.8-12MM)(EF) ColorVu - 8.3 Mpx 4K UHD MOTOZOOM Hikvision	IP CAMERA IDS-2CD7A86G0-IZHSY(2.8-12MM) - 8.3 Mpx 4K UHD 2.8 ... 12 mm - MOTOZOOM Hikvision	IP CAMERA BCS-L-TIP48VSR6-AI1 - 8.3 Mpx 4K UHD 2.7 ... 13.5 mm - MOTOZOOM BCS Line	IP CAMERA BCS-L-TIP58VSR6-AI1-G - 8.3 Mpx 4K UHD 2.7 ... 13.5 mm - MOTOZOOM BCS Line
	683.33 EUR 683.33 EUR	739.24 EUR 739.24 EUR	1422.09 EUR 1422.09 EUR	417.88 EUR 417.88 EUR	551.68 EUR 551.68 EUR
Standard	TCP/IP	TCP/IP	TCP/IP	IP	TCP/IP
Matrix size	8 Mpx	8.3 Mpx	8.3 Mpx 4K UHD	...	8.3 Mpx 4K UHD
Sensor	1/1.8 " Progressive Scan CMOS	1/1.8 " Progressive Scan CMOS	1/1.8 " Progressive Scan CMOS	1/2.8 " Progressive Scan CMOS	1/2.8 " Progressive Scan CMOS
Resolution	3840 x 2160 - 8.3 Mpx, 4K UHD , 3200 x 1800 - 5.8 Mpx , 2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p	3840 x 2160 - 8.3 Mpx 4K UHD , 3200 x 1800 - 5.7 Mpx , 2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p	3860 x 2160 - 8.3 Mpx 4K UHD , 3072 x 1728 - 5.3 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p	3840 x 2160 - 8.3 Mpx 4K UHD , 3072 x 2048 - 6 Mpx , 3072 x 1728 - 5 Mpx , 2592 x 1944 - 5 Mpx , 2688 x 1520 - 4 Mpx , 2048 x 1536 - 3 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p	3840 x 2160 - 8.3 Mpx 4K UHD , 3072 x 2048 - 6 Mpx , 3072 x 1728 - 5 Mpx , 2592 x 1944 - 5 Mpx , 2688 x 1520 - 4 Mpx , 2560 x 1440 - 3.7 Mpx , 2048 x 1536 - 3 Mpx , 2304 x 1296 - 3 Mpx , 1920 x 1080 - 1080p , 1280 x 960 - 1.3 Mpx , 1280 x 720 - 720p
Lens	2.8 ... 12 mm - Motozoom	2.8 ... 12 mm Motozoom	2.8 ... 12 mm - Motozoom	2.7 ... 13.5 mm - Motozoom	2.7 ... 13.5 mm - Motozoom
White light LED illuminator range	...	60 m	...	...	...
View angle	• 108 ° ... 46 ° (manufacturer data) • 104 ° ... 46 ° (our tests result)	112 ° ... 41 °	112 ° ... 41 ° (manufacturer data)	113 ° ... 31 °	• 109 ° ... 30 ° (manufacturer data) • 104 ° ... 31 ° (our tests result)
Min. illumination	...	...	...	...	...
S/N ratio	...	...	...	...	...
Compression	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG	H.265+ / H.265 / H.264+ / H.264 / MJPEG	H.265+ / H.265 / H.264+ / H.264 / MJPEG / AI Coding
Range of IR illumination	60 m	60 m	50 m	60 m	60 m
Image compression method	...	H.265+ / H.265 / H.264+ / H.264 / MJPEG	...	...	...
Access from PC	...	...	...	Port no.: 37777 or access by a cloud (P2P) PC: Free application BCS Manager	...
Interface	...	...	...	...	...
Alarm inputs / outputs	1 / 1	1 / 1	2 / 2	1 / 1	1 / 1
Main stream frame rate	25 fps - 8.3 Mpx	25 fps @ 8.3 Mpx	25 fps - 8.3 Mpx	25 fps - 8 Mpx	25 fps - 8.3 Mpx
Network interface	10/100 Base-T (RJ-45)	10/100 Base-T (RJ-45)	10/100/1000 Base-T (RJ-45)	...	10/100 Base-T (RJ-45)
Wiegand interface	...	...	—	...	...
Intelligent image analysis	...	...	...	• intrusion • crossing the line (tripwire) • Vehicle / human recognition	...

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00