

Code: BCS-TIP5801IR-V-VI

# IP CAMERA **BCS-TIP5801IR-V-VI** - 8.3 Mpx 4K UHD 2.7 ... 13.5 mm - MOTOZOOM BCS Line

Net: **219.94 EUR** Gross: **219.94 EUR**

IP camera with efficient H.264 / H.265 image compression algorithm for clear and smooth video streaming at maximal resolution of 8.3 MPx, 4K UHD. Due to above it is perfect solution for surveillance systems requiring persons or vehicles recognition.

The used motozoom lens with 2.7 ... 13.5 mm focal length allows to remote view angle adjustment.

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install. Camera is according to IP67 Index of Protection norm.



## SPECIFICATION

|                           |                                                                                                                                                                                                                                                              |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standard:                 | TCP/IP                                                                                                                                                                                                                                                       |
| Sensor:                   | 1/2.7 "<br>Progressive Scan CMOS                                                                                                                                                                                                                             |
| Matrix size:              | 8.3 Mpx 4K UHD                                                                                                                                                                                                                                               |
| Resolution:               | 3840 x 2160 - 8.3 Mpx 4K UHD ,<br>3072 x 2048 - 6 Mpx ,<br>3072 x 1728 - 5 Mpx ,<br>2592 x 1944 - 5 Mpx ,<br>2688 x 1520 - 4 Mpx ,<br>2048 x 1536 - 3 Mpx ,<br>2304 x 1296 - 3 Mpx ,<br>1920 x 1080 - 1080p ,<br>1280 x 960 - 1.3 Mpx ,<br>1280 x 720 - 720p |
| Lens:                     | 2.7 ... 13.5 mm - Motozoom                                                                                                                                                                                                                                   |
| View angle:               | • 113 ° ... 31 ° (manufacturer data)<br>• 107 ° ... 32 ° (our tests result)                                                                                                                                                                                  |
| Compression:              | H.265+ / H.265 / H.264+ / H.264 / MJPEG                                                                                                                                                                                                                      |
| Range of IR illumination: | 60 m                                                                                                                                                                                                                                                         |
| Alarm inputs / outputs:   | —                                                                                                                                                                                                                                                            |
| Main stream frame rate:   | • 15 fps @ 8 Mpx<br>• 25 fps @ 4 Mpx                                                                                                                                                                                                                         |
| Network interface:        | 10/100 Base-T (RJ-45)                                                                                                                                                                                                                                        |
| Audio:                    | —                                                                                                                                                                                                                                                            |

|                                |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|--------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| WEB Server:                    | Built-in                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Memory card slot:              | Micro SD memory cards up to 256GB support (possible local recording)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Max. number of on-line users:  | 20                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| ONVIF:                         | ✓                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Mobile phones support:         | Port no.: 37777 or access by a cloud (P2P)<br>• Android: Free application <a href="#">BCS Manager</a><br>• iOS (iPhone): Free application <a href="#">BCS Manager</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Default admin user / password: | admin / -<br>The administrator password should be set at the first start                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Default IP address:            | 192.168.1.108                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Web browser access ports:      | 80, 37777                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| PC client access ports:        | 37777                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Mobile client access ports:    | 37777                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Port ONVIF:                    | 80                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| RTSP URL:                      | rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream<br>rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| RS-485 interface:              | —                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Main features:                 | <ul style="list-style-type: none"> <li>• WDR - 120 dB - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ROI - improve the quality of selected parts of image</li> <li>• NAS - Network Attached Storage support</li> <li>• BLC - Back Light Compensation</li> <li>• HLC - High Light Compensation (spot)</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• Motion Detection - max. 4 zones</li> <li>• Privacy zones - max. 4</li> <li>• Auto White Balance</li> <li>• Mirror - Mirror image</li> <li>• IVS analysis : crossing the line (tripwire), intrusion</li> </ul> |
| Power supply:                  | <ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 830 mA</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Power consumption:             | ≤ 9.9 W                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Housing:                       | Compact, Metal                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Color:                         | White                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| "Index of Protection":         | IP67                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Operation temp:                | -30 °C ... 60 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Supported languages:           | Polish, English                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Weight:                        | 0.72 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Dimensions:                    | 244 x 90 x 90 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Manufacturer / Brand:          | BCS Line                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Guarantee:                     | <b>3 years</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

## PRESENTATION

Front view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60



Side view:



Memory card slot and "Reset" button:



Mounting side view:



Dimensions:



In the kit:



## OUR TESTS


Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



## OUR OPINIONS



- Motozoom lens.

## PACKAGE

|                                  |                    |
|----------------------------------|--------------------|
| Dimensions (L x W x H): 0x0x0 mm | Gross Weight: 0 kg |
|----------------------------------|--------------------|



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
 POL; 60-713 Poznań; Graniczna 10  
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60