

Code: 24V/4.2A/GPV-MINI

SWITCHING ADAPTER 24V/4.2A/GPV-MINI

Net: 151.98 DKK Gross: 151.98 DKK

Hermetic power supply in a plastic housing.

Attention! If the power adaptor is using for continuous work (24H) the rated current of the adaptor should be less than 80% of the maximal current.

Please pay attention for proper cooling conditions of the power adaptor during work!



SPECIFICATION

Adapter type:	Switching
Power voltage:	190 ... 264 V AC
Frequency range:	50 / 60 Hz
Output voltage:	24 V DC
Output voltage tolerance:	± 5 %
Maximal load:	4.2 A
Output power:	100.8 W
Efficiency:	90 %
Number of outputs:	1 pcs
Protections:	• Overload • Short-circuit • Overvoltage • Overheat
Main features:	• Protection class : II • Box casing designed to wall mounting
Housing type:	Plastic, Waterproof
"Index of Protection":	IP67
Operation temp:	-20 °C ... 70 °C
Weight:	0.39 kg
Dimensions:	162 x 42 x 34 mm
Guarantee:	3 years

PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------