

Code: AT-UPS850P-LED

UPS **AT-UPS850P-LED** 850 VA EAST

Net: **68.01 EUR** Gross: **68.01 EUR**

The AT-UPS850P-LED UPS has been equipped with a number of advanced technologies ensuring active monitoring of the power supply network. The device works with power supply adapters having Active Power Factor Correction (APFC).



SPECIFICATION

Nominal power:	510 W
Apparent Power:	850 VA
Input voltage:	165 V ... 275 V AC
Input frequency:	50 / 60 Hz (auto detection)
Output voltage:	230 V AC $\pm$ 10 % (Approximated Sine Wave)
Output frequency:	50 / 60 Hz $\pm$ 1 %
Transfer time:	$\leq$ 10 ms
Charging time (recover to 90% capacity):	8 hours
Battery:	1 pcs - 12V/8Ah
Estimated battery operation time:	• 23 minutes @ 100 W • 5 minutes @ 300 W • 2 minutes @ 500 W
Number of outputs:	4 pcs CEE 7/3 (Schuko)
Protections:	• Glass Fuse • Overvoltage • Overload protection • Overcharge protection • Telephone line filter
Operation state indication:	• LED diodes, • Sound signaling

Main features:	• Automatic Voltage Regulator (AVR) • Compatible with power generators • Remote management - UPSmart application included • Built-in EMI, RFI filter • Configurable alarm
Application:	• Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment
Housing type:	Desktop
Operation temp. / Relative humidity:	0 °C ... 40 °C / 20 ... 90 %
Weight:	5.7 kg
Dimensions:	280 x 185 x 95 mm
Manufacturer / Brand:	EAST
Guarantee:	2 years

PRESENTATION

Top view:



Side view:





Bottom view:



In the kit:



PACKAGE

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

