

Code: ROUTERUPS-30-POE

UPS **ROUTERUPS-30-POE** 30 W 5 V / 9 V / 12 V DC, 15 V / 24 V PoE IPS

Net: **55.45 EUR** Gross: **55.45 EUR**

The UPS is designed to power devices with low power consumption, such as a router. The device has a small casing, economical design and automatic start in the absence of mains power.

The UPS has a built-in PoE 15V/24V interface to provide data transmission and power through a single RJ-45 connector.



SPECIFICATION

Nominal power:	30 W
Apparent Power:	—
Input voltage:	100 ... 240 V AC
Input frequency:	50 / 60 Hz
Output voltage:	5 V / 9 V / 12 V DC, 15 V / 24 V PoE
Battery:	4 pcs Li-Ion - 3.7 V / 2.2 Ah
Number of outputs:	• 1 x USB-A socket, • 1 x 2.1/5.5 mm socket - 9 / 12 V (switchable), • 1 x RJ-45 socket / Port LAN & PoE - 15 / 24 V (switchable), • 1 x RJ-45 socket / Port LAN
Maximal outputs load:	• 2 A @ 5 V USB • 2 A @ 9 V (2.1/5.5mm socket) • 2 A @ 12 V (2.1/5.5mm socket) • 1 A @ 15 V (RJ-45 socket) • 1 A @ 24 V (RJ-45 socket)
Operation state indication:	LED diodes : Status, 9V output, 12V output, Battery charging 25 % / 50 % / 75 % / 100 %
Protections:	• Overload • Discharge • Short-circuit
Main features:	• Auto restart while AC is recovering • COLD START: - Cold start of the power adapter • Overload signaling • Battery charging indication • PoE power mode - wires : 4-5(+), 7-8(-) • RESET button
Application:	• Router / Access Point / Switch • Charging the devices, eg. smartphones, etc. • CCTV cameras
Housing type:	Desktop
Operation temp. / Relative humidity:	0 °C ... 40 °C / 20 ... 90 %

Weight:	0.38 kg
Dimensions:	160 x 105 x 28 mm
Manufacturer / Brand:	IPS
Guarantee:	2 years

PRESENTATION



Front view:



Rear view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------