

Code: VI-3000-RT/LCD

UPS VI-3000-RT/LCD 3000 VA

Net: 912.08 EUR Gross: 912.08 EUR

The VI-3000-RT/LCD UPS is a professional device used to maintain the operation of the components connected to it. Additionally protects the connected equipment against overvoltages.



SPECIFICATION

Nominal power:	2700 W
Apparent Power:	3000 VA
Input voltage:	161 ... 276 V AC
Input frequency:	50 / 60 Hz $\pm$ 5 % at standard mode > 40 Hz at generator mode
Output voltage:	220 / 230 / 240 V AC (Pure Sine Wave)
Voltage adjustment:	$\pm$ 5 % RMS for whole range of battery voltages
Frequency adjustment:	$\pm$ 0.1 % (battery mode)
Estimated battery operation time:	4 minutes (at full load)
Charging time (recover to 90% capacity):	4 hours
Battery:	6 x 12V/9Ah
Number of outputs:	8 pcs
Transfer time:	2 ... 6 ms (max. 10 ms) (13ms at generator mode)
Additional protection:	RJ11, RJ45
Management software:	WinPower (Windows 98/2000/XP/Vista/7/8, MAC, Linux, FreeBSD, Solaris)
Protections:	• Overload protection

Main features:	• Auto restart while AC is recovering • GreenPower UPSTM Technology • EPO (Emergency power off) function • Automatic Voltage Regulator (AVR) • UPS auto diagnostic system • Smart battery charging to extend battery lifetime • Intelligent cooler system control to reduce the noise level • USB/RS-232 communication port • LCD, audio messages • Alarms indication on LCD: blue, red, blinking red based on UPS status • 4 x ICE C13 programmable outlets • Battery charging at power-off mode • "Cold Start" function • Energy Saving function (possibility to deactivate from software)
Application:	• medium-sized enterprise • Surveillance Systems • data storage centers • network, servers, workstations • Industrial Equipment
Housing type:	Rack/Tower 2-in-1 Design
Operation temp. / Relative humidity:	0 °C ... 40 °C / 20 ~ 90 % (non-condensing)
Dimensions:	438 x 608 x 86.5 mm
Weight:	30.4 kg
Guarantee:	2 years

PRESENTATION

UPS is equipped with large readable LCD display:



Device connectors:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

