

Code: DS-QAE1A80G1-VB

2-ZONE NETWORK AMPLIFIER **DS-QAE1A80G1-VB** 80 W Hikvision

Net: **312.84 EUR** Gross: **312.84 EUR**

The amplifiers supply the speakers with an audio signal with an appropriately elevated voltage and power matched to the load. The DS-QAE1A80G1-VB amplifier is a mixer amplifier, that is, an amplifier integrated with a mixer, equipped with microphone input, 2 line inputs, USB player and Bluetooth interface. The amplifier has a built-in mixer with adjustable gain levels for individual input channels and 2 line outputs to an external amplifier, and 2 speaker outputs (100 V).

The built-in webserver allows to support playback schedules saved in memory. The **HIKCentral Professional** application is dedicated to management.

The mixer amplifier is a good solution for smaller installations where a simple and compact system is needed.



SPECIFICATION

Nominal power:	80 W (2 x 40 W @ 100 V)
Bandwidth:	80 Hz ... 20 kHz
S/N ratio:	≥ 100 dB
Audio input level adjustment:	<ul style="list-style-type: none">• Microphone• RCA 1 input• RCA 2 input
Audio inputs:	<ul style="list-style-type: none">• 1 pcs Jack 6.5 mm socket - External microphone input,• 2 pcs CINCH MONO,• 1 pcs USB 2.0,• Bluetooth
Audio outputs:	<ul style="list-style-type: none">• 2 pcs CINCH,• 2 pcs Speaker output - 100V line connector
Alarm inputs / outputs:	1 / 1
LED indication:	Power, USB, Bluetooth
Internal memory:	4 GB eMMC (1 GB : Audio)
Supported audio formats:	64 kbps G.711, 128 kbps MP3
Interface:	Ethernet (RJ45) 10/100 Mb
Network protocols:	IPv4, HTTP, HTTPS, SSL / TLS, DNS, NTP, TCP, UDP, IGMP, ICMP, DHCP, ARP, SSH, ISAPI, ISUP, RTP
Management software:	HIKCentral Professional
Main features:	<ul style="list-style-type: none">• Bluetooth interface• Multimedia playback from USB memory : MP3, WAV• Web-Server built-in• Input channel mixing• Support for playback schedules stored in internal memory (1GB)• Synthesize recorded messages in English - female/male voice to select (CH1)
Protections:	<ul style="list-style-type: none">• Short-circuit• Overload• Temperature• Built-in ESD protection• Overvoltage protection• Electric shock protection

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Housing:	Plastic
Color:	White
Power supply:	24 V DC / 5 A (power adapter included)
Operation temp:	-10 °C ... 55 °C
Weight:	1.51 kg
Dimensions:	231 x 220 x 51 mm
Manufacturer / Brand:	Hikvision
SAP Code:	347000001
Guarantee:	3 years

PRESENTATION

Front view:



Rear view:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------