

Code: 12V/2.5A-GTPCS

SWITCHING ADAPTER 12V/2.5A-GTPCS

Net: 136.24 SEK Gross: 136.24 SEK

GTPCS series power supplies are a great solution wherever there is little space for installation. Thanks to their flat housing and small size, they are ideal for use in the furniture and advertising industries. A very important advantage of the device is compliance with the standards: EN 55015, EN 62493, EN 61547, EN 61000-3-3, EN 61000-3-2.

Attention! If the power adaptor is using for continuous work (24H) the rated current of the adaptor should be less than 80% of the maximal current.

Please pay attention for proper cooling conditions of the power adaptor during work!



SPECIFICATION

Adapter type:	Switching
Power voltage:	180 ... 264 V AC
Frequency range:	50 / 60 Hz
Output voltage:	12 V DC
Maximal load:	2.5 A
Output power:	30 W
Number of outputs:	1 pcs
Protections:	<ul style="list-style-type: none">• Overload• Short-circuit• Overvoltage
Housing type:	Plastic
Operation temp:	-10 °C ... 70 °C
Main features:	Box casing designed to wall mounting
Weight:	0.11 kg
Dimensions:	251 x 30 x 16.5 mm
Guarantee:	2 years

PRESENTATION



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Top view:



Connectors:





Dimensions:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------