







	WIRELESS GLASS BREAK DETECTOR AGD-200 (Glass Break Detector) ABAX/ABAX2 SATEL	WIRELESS GLASS BREAK DETECTOR AGD-200-BR (Glass Break Detector BR) SATEL	WIRELESS GLASS BREAK DETECTOR AGD-200-DG (Glass-Break-Detector-DG) SATEL	WIRELESS ACOUSTIC GLASS BREAK DETECTOR AX PRO DS-PDBG8-EG2-WE Hikvision	WIRELESS GLASS BREAK DETECTOR MGD-300 SATEL	WIRELESS GLASS BREAK DETECTOR MGD-300-BR SATEL
						
	61.64 EUR 61.64 EUR	61.64 EUR 61.64 EUR	61.64 EUR 61.64 EUR	65.70 EUR 65.70 EUR	32.25 EUR 32.25 EUR	32.25 EUR 32.25 EUR
Detection	detection of breaking plate, laminated or tempered glass	detection of breaking plate, laminated or tempered glass	detection of breaking plate, laminated or tempered glass	Glass break detector	Glass break detector	Glass break detector
Range	max. 8 m
Detection angle	120 °
Sensitivity adjustment	2, 4, 6, 8 m
Frequency band	868 MHz ... 868.6 MHz	868 MHz ... 868.6 MHz	868 MHz ... 868.6 MHz	...	433.05 MHz ... 434.79 MHz	433.05 MHz ... 434.79 MHz
Support	ABAX/ABAX2	Satel ABAX/ABAX2	Satel ABAX/ABAX2	HIKVISION AX PRO	Satel MICRA, PERFECTA	Satel MICRA
Tamper contact	✓	✓
Alarm signaling	Signal to control panel	Signal to control panel	Signal to control panel	• LED indicator : Color - blue, • Signal to control panel	Signal to control panel	Signal to control panel
Protection class (Grade)	—	—
Frequency range	868 MHz - Tri-X Wireless
Environmental class EN 50130-5	II	II
Radio communication range (at open area)	• ~ 500 m @ ABAX, • ~ 2000 m @ ABAX2	• ~ 500 m @ ABAX , • ~ 2000 m @ ABAX2	• ~ 500 m @ ABAX , • ~ 2000 m @ ABAX2	max. 1600 m	max. 200 m	max. 200 m
Alarm inputs	NO/NC
Battery	CR123A 3 V - 3.0 V (included)	CR123A 3 V - 3.0 V (included)	CR123A 3 V - 3.0 V (included)	...	CR123A 3 V	CR123A 3 V
Power supply	2 x battery CR123A 3 V (included)
Backup time	~ 2 years	~ 2 years	~ 2 years	~ 5 years	max. 3 years	max. 3 years
Current consumption	max. 24 mA	18 mA	18 mA
Permissible relative humidity	93 ± 3 %	93 ± 3 %
Main features	<ul style="list-style-type: none"> • advanced dual-path microprocessor signal analysis • Remote configuration • Tamper protections 	<ul style="list-style-type: none"> • advanced dual-path microprocessor signal analysis • Remote configuration • Tamper protections 	<ul style="list-style-type: none"> • advanced dual-path microprocessor signal analysis • Remote configuration • Tamper protections 	<ul style="list-style-type: none"> • The sensor operation is based on omni-directional high quality microphone • detection of breaking plate, laminated or tempered glass - Glass thickness : 2.4 mm ... 6.4 mm, Glass size : 0.3 m x 0.3 m ... 3 m x 3 m • Digital detector • Signal indicator • Bidirectional communication • AES-128 data encryption • Frequency hopping against jamming for reliable transmission • Tamper detection - opening the enclosure, removing from mounting surface • Remote management 	<ul style="list-style-type: none"> • Plate, laminated, tempered glass breaking • Test mode • trimmer sensitivity adjustment 	<ul style="list-style-type: none"> • Plate, laminated, tempered glass breaking • Test mode • trimmer sensitivity adjustment
Environment class	II
Color	White	Brown	Dark graphite	White	White	Brown
Operation temp	-10 °C ... 55 °C	-10 °C ... 55 °C	-10 °C ... 55 °C	-10 °C ... 55 °C	-10 °C ... 55 °C	-10 °C ... 55 °C
Weight	0.02 kg	0.02 kg	0.02 kg	0.08 kg	0.04 kg	0.04 kg
Dimensions	20 x 102 x 23 mm	20 x 102 x 23 mm	20 x 102 x 23 mm	24 x 107 x 39 mm	25 x 111 x 28 mm	25 x 111 x 28 mm
Manufacturer / Brand	SATEL	SATEL	SATEL	Hikvision	SATEL	SATEL
SAP Code	314300119
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years

DELTA-OPTI Monika Matysiak / VAT:PL5251295225 / 60-713 Poznań, ul. Graniczna 10
Tel:+48 61 864 69 60 / GSM:+48 607 60 11 66 / Fax:+48 61 864 69 65 / e-mail: info@delta.poznan.pl
Monday-Friday: 8.00-19.00 / Saturday: 8.00-14.00