

Code: TRISET-113PE

COAXIAL CABLE TRISET-113PE

Net: 0.56 EUR Gross: 0.56 EUR

The TRISET-113PE is modern 75 Ω impedance coaxial cable with very good electric and mechanical parameters. For convenience, cable is marking with length counter printed with 1 m distance step. The cable is made with PE coating (polyethylene), so it can be used outdoors. **The cable is gel-fitted.**



SPECIFICATION

In section:	100 m . Price for 1m when buying a whole roll
Coaxial cable:	TRISET
Inner conductor:	Ø 1.13 mm Cu Wire
Dielectric:	Ø 4.8 mm (physical foam)
Shield:	Al/PET/Al - 9 μ m / 23 μ m / 9 μ m
Braid:	81 % Al wire
Outer coating:	Ø 6.8 mm PE + gel
Coating color:	Black
Resistance of the inner conductor for DC current:	16.85 Ω /km
Capacity:	52 pF/m
Dielectric resistance:	2000 M Ω /km
Shortening wave coefficient:	84 %
Impedance:	75 Ω
Main features:	• low attenuation • perfect matched • high screening efficiency • PE coating • Class A compliance
Cable attenuation at 100m section:	4.5 dB @ 47 MHz 5.8 dB @ 88 MHz 8.0 dB @ 174 MHz 9.2 dB @ 230 MHz 13.2 dB @ 470 MHz 18.1 dB @ 862 MHz 20.1 dB @ 950 MHz 27.7 dB @ 2150 MHz 30.8 dB @ 2400 MHz
Guarantee:	2 years


PRESENTATION



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



LABORATORY TESTS RESULTS:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm Gross Weight: 0 kg