

Code: SCO-2120RP

CAMERA **SCO-2120RP** 3.9 ... 46 mm

Net: **1 350.01 PLN** Gross: **1 350.01 PLN**

The SCO-2120RP camera is equipped with perfect Sony Super HAD CCD sensor. The 3 Axis bracket allows also to mount the camera to the ceiling. Cables are hidden inside bracket, it protects against cutting them and improves the aesthetics of installation. Camera is according to IP66 Index of Protection norm.



SPECIFICATION

Sensor:	1/4 " Sony Super HAD CCD
Resolution:	600 TVL (color) 700 TVL (B/W)
Lens:	3.9 ... 46 mm
View angle:	52 ° ... 4.5 °
Range of IR illumination:	70 m
RS-485 interface:	✓
S/N ratio:	> 52 dB
Video output:	1 Vpp / 75 Ω
Power supply:	12 V / 580 mA
Main features:	<ul style="list-style-type: none">• Motozoom• ICR - Movable InfraRed filter• DIS - Digital Image Stabilization• Sense-UP - (Slow Shutter) - Increase the sensor sensitivity• SSNR3 (DNR)• SSSDR (WDR)• BLC - configurable Back Light Compensation• HLC - High Light Compensation (spot)• Privacy zones• Motion Detection• Mirror• D-ZOOM - Digital Zoom
Housing:	Metal
Color:	Dark graphite
"Index of Protection":	IP66
Operation temp:	-10 °C ... 50 °C
Weight:	1.1 kg
Dimensions:	275 x 119 x 86 mm
Guarantee:	2 years

PRESENTATION



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Camera view after remove the Dome cover:



Side view:



In the kit:



Dimensions:



Package:



OUR TESTS

Screen shots from camera tests:

Camera image at artificial illumination (about 30Lux):

Zoom x1: Zoom x5: Zoom x12:



Camera image at night conditions with internal built-in IR illuminator on:



Camera image at direct strong light opposite to camera:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------