

	OPTICAL RETRANSMITTER GL-FIBRE-020/RPT	SATELLITE OPTICAL RECEIVER GL-FIBRE-JRS- GTU/MKII QUATRO	SPLITTER RL-2/1E-SAT-RL	SPLITTER RL-2/1E-SAT-SIG	SPLITTER RL-3/1E-SAT-OPTI OPTICUM	SPLITTER RL-3/1E-SAT-SIG	SPLITTER RL-4/1E-SAT-OPTI OPTICUM	SPLITTER RL-4/1E-SAT-OPTI OPTICUM	SPLITTER RL-4/1E-SAT-SIG	SPLITTER RL-6/1E-SAT-OPTI OPTICUM	SPLITTER RL-6/1E-SAT-SIG	TV/SAT SPLITTER SD-504	TV/SAT SPLITTER SD-515	TV/SAT SPLITTER SD-904 TERRA	TV/SAT SPLITTER SDQ-508 TERRA	TV/SAT SPLITTER SDQ-908 TERRA
																
	314.77 EUR 314.77 EUR	131.34 EUR 131.34 EUR	3.33 EUR 3.33 EUR	2.43 EUR 2.43 EUR	1.80 EUR 1.80 EUR	3.28 EUR 3.28 EUR	1.84 EUR 1.84 EUR	3.82 EUR 3.82 EUR	6.64 EUR 6.64 EUR	3.73 EUR 3.73 EUR	6.84 EUR 6.84 EUR	40.63 EUR 40.63 EUR	45.63 EUR 45.63 EUR	72.89 EUR 72.89 EUR	86.03 EUR 86.03 EUR	159.01 EUR 159.01 EUR
Number of inputs	1 pcs FC/UPC	...	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	1 pcs	...	...	9 pcs	5 pcs	9 pcs
Number of outputs	2 pcs FC/UPC	...	2 pcs	2 pcs	3 pcs	3 pcs	4 pcs	6 pcs	6 pcs	8 pcs	8 pcs	...	...	18 pcs	20 pcs	36 pcs
Attenuation	...	...	3.5 dB	6 dB	8 dB	8 dB	< 11.9 dB	< 15.9 dB	12 dB	< 15.9 dB	15 dB	...	...	...	...	...
Input signal level	-12 dBm ... -3 dBm	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Possibility to pass the DC voltage to the preamplifier	...	...	...	✓	✓	✓	✓	✓	✓	✓	✓	...	...	...	...	...
Output signal level	7 dBm	...	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Shielding	...	...	✓	✓	✓	✓	✓	✓	✓	✓	✓	...	...	...	...	...
Impedance	...	...	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	75 Ω	...	...	...	...	...
Frequency range	...	• 88 ... 108 MHz - FM, • 174 ... 240 MHz - DAB, • 470 ... 790 MHz - DVB-T/T2, • 950 ... 2150 MHz - SAT	5 ... 2400 MHz	5 ... 2300 MHz	5 ... 2450 MHz	5 ... 2300 MHz	5 ... 2450 MHz	5 ... 2450 MHz	5 ... 2300 MHz	5 ... 2450 MHz	5 ... 2300 MHz	950 ... 2400 MHz - SAT, 5 ... 862 MHz - TV	950 ... 2400 MHz - SAT, 5 ... 862 MHz - TV	• 950 ... 2400 MHz - SAT, • 5 ... 862 MHz - RTV	• 950 ... 2400 MHz - SAT, • 5 ... 862 MHz - RTV	• 950 ... 2400 MHz - SAT, • 5 ... 862 MHz - RTV
Connection loss	...	...	...	...	...	...	...	...	...	...	...	4 dB - SAT, 4 dB - TV	15 ... 16 dB - SAT, 13 ... 17 dB - TV	4 dB - SAT, 4 dB - RTV	• 8 dB - SAT • 8 dB - RTV	• 8 dB - SAT • 8 dB - RTV
Housing	...	...	• For outdoor use • Splash-proof casing • Plastic	...	...	...	...	...	...	...	...	...	...	...	...	...
Isolation between outputs	...	...	...	16 dB	...	16 dB	...	...	...	...	...	> 30 dB	> 30 dB	> 30 dB	> 30 dB	30 dB
DC-transition	...	...	...	...	...	...	...	...	...	...	...	max. 2 A	max. 2 A	max. 2 A	max. 2 A	max. 2 A
Mount	...	...	To the mast, To the wall	...	...	...	...	...	...	...	...	...	...	...	...	...
Main features	...	...	Recommended for UNICABLE system - single-cable technology	...	...	...	...	...	...	...	...	...	...	The die-cast metal body provides effective shielding and high mechanical resistance	The die-cast metal body provides effective shielding and high mechanical resistance	• 8 path SAT + RTV terrestrial splitter • The die-cast metal body provides effective shielding and high mechanical resistance
Operation temp	-10 °C ... 50 °C	...	...	...	...	...	...	...	...	...	...	-20 °C ... 50 °C	-20 °C ... 50 °C	-20 °C ... 50 °C	-20 °C ... 50 °C	-20 °C ... 50 °C
Manufacturer / Brand	...	...	...	...	OPTICUM	...	OPTICUM	OPTICUM	...	OPTICUM	...	...	...	TERRA	TERRA	TERRA
SAT RF outputs	...	• 18 V / 22 kHz - HH • 13 V / 22 kHz - VH • 18 V / 0 kHz - HL • 13 V / 0 kHz - VL	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Output level	...	• 79 dBμV - SAT, • 68 dBμV - DVB-T/T2	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Optical wavelength	1100 nm ... 1650 nm	1100 nm ... 1650 nm	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Optical connector type	...	FC/PC	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Power supply	20 V DC / 150 mA (F connector) - Power adapter included	10.5 V ... 21 V DC	...	...	...	...	...	...	...	...	...	...	...	...	...	...
Weight	0.17 kg	0.17 kg	0.073 kg	0.09 kg	0.04 kg	0.1 kg	0.04 kg	0.1 kg	0.16 kg	0.1 kg	0.16 kg	0.39 kg	0.4 kg	0.75 kg	0.77 kg	1.5 kg
Dimensions	108 x 76 x 26 mm	121 x 80 x 26 mm	77 x 68 x 44 mm	60 x 50 x 25 mm	73 x 46 x 17 mm	85 x 55 x 20 mm	73 x 46 x 17 mm	120 x 57 x 23 mm	120 x 60 x 20 mm	120 x 57 x 24 mm	120 x 60 x 20 mm	126 x 135 x 30 mm	126 x 135 x 30 mm	126 x 135 x 50 mm	267 x 135 x 30 mm	267 x 135 x 51 mm
Guarantee	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years