

Code: OV-8D/SC

FIBER OPTIC VIDEO CONVERTER **OV-8D/SC** 8x VIDEO + RS-485 TXRX SET

Net: **304.28 EUR** Gross: **304.28 EUR**

The OV-8D/SC allows to transmit video channels and telemetry data channel RS-485 via one single mode fiber up to 20 km or one multi mode fiber up to 2 km. The device is equipped with SC connector ensuring reliable connections. Is compatible with PAL/SECAM/NTSC systems and ensures high quality transmission of live video over distances up to 20 km, much longer than those offered by standard devices. The transmitter and receiver set enables the highest image quality and possibility to transmit telemetry data channel RS-485 from receiver to transmitter allowing to Speed Dome cameras control.



SPECIFICATION

Optical connector type:	SC
Number of fibers:	1 pcs
Recommended fiber:	Single-mode or multi-mode fiber
Transmission range:	20 km Single-mode fiber 2 km Multi-mode fiber
Number of video channels:	8 pcs PAL / NTSC / SECAM
Video connectors type:	BNC
Video resolution:	10 bit (manufacturer data) 8 bit (our tests result)
Video bandwidth:	0 MHz ... 7.5 MHz
Video input voltage / impedance:	1 Vpp / 75 Ω
Audio input:	—
RS-485 signal:	one-direction RS-485 Connectors 1 (-), 2 (+) - terminals
Optical wavelength:	1310 / 1550 nm
S/N ratio:	≥ 70 dB
Power supply:	5 V DC / 1.2 A (power adapter included)
Operation temp:	-40 $^{\circ}$ C ... 85 $^{\circ}$ C
LED diodes:	LEDs indicating device operation state
Permissible relative humidity:	0 % ... 95 % (non-condensing)
Weight:	0.720 kg

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Dimensions:	189 x 174 x 51 mm
Guarantee:	2 years

PRESENTATION

Front panel of the transmitter (with letter T) and receiver (with letter R):



Rear panel:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------