

Code: SO-MF3-W

## PROXIMITY READER **SO-MF3-W** SATEL

Net: **106.09 EUR** Gross: **106.09 EUR**

Proximity card reader.



### SPECIFICATION

Cards support:	13.56 MHz S50 : Ultralight CSN/SSN, Classic CSN/SSN/MSN, DESFire (EV1 / EV2 / EV3) CSN/MSN
Reading distance of prox-keys:	max. 5 cm
Relay output:	1 pcs
Relay contacts rating (resistive load):	1 A / 30 V
Keyboard built-in:	—
Autonomous operation:	✓
Operation modes:	<ul style="list-style-type: none"><li>• Proximity card reader for INTEGRA alarm system,</li><li>• Proximity card reader for ACCO NET or ACCO access control system,</li><li>• Wiegand Reader,</li><li>• standalone door control module</li></ul>
Tamper output:	✓
Communication:	<ul style="list-style-type: none"><li>• Wiegand 26-66bit</li><li>• Open Supervised Device Protocol (OSDP)</li><li>• EM-MARIN</li></ul>
Main features:	<ul style="list-style-type: none"><li>• Tamper protection (detection of removing from mounting surface and enclosure opening)</li><li>• LED indication</li><li>• Beep signal</li></ul>
Color:	White
Power supply:	12 V DC
Average current consumption:	63 mA

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60

Operation temp:	-25 °C ... 55 °C
Permissible relative humidity:	max. 93 %
Weight:	0.09 kg
Dimensions:	128 x 45 x 21 mm
Manufacturer / Brand:	SATEL
Guarantee:	2 years

## PRESENTATION

Front panel:



Internal view of the housing:





Rear view:

NC ○ ○ +12V  
 C ○ ○ COM  
 NO ○ ○ CLK/D0  
 DATA/D1 ○ ○ IN1  
 RSA ○ ○ IN2  
 RSB ○ ○ IN3  
 TMP ○ ○ BELL

Satel MINI: 181106395  
 P70-SOMP3V15P10101-00  
 Data produkcji: 2024-04-11

NC ○ ○ +12V  
 C ○ ○ COM  
 NO ○ ○ CLK/D0  
 DATA/D1 ○ ○ IN1  
 RSA ○ ○ IN2  
 RSB ○ ○ IN3  
 TMP ○ ○ BELL

Satel MINI: 181106395  
 P70-SOMP3V15P10101-00  
 Data produkcji: 2024-04-11



In the kit:



## PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------