

Code: ATLO-KRM-203

CODE LOCK ATLO-KRM-203

Net: 180.23 SEK Gross: 180.23 SEK

Indoor, autonomous code lock with RFID reader.

Autonomous operation of the device allows the user to:

- Open by using a card or PIN code.
- Remember stored cards or PIN codes.
- Signaling left the door open.
- Acoustic and optical signaling.

Administrator capabilities are following:

- Programming by using the keypad.
- Adding a new card by using the keypad.

Attention! No backlit keyboard.



SPECIFICATION

Cards support:	13.56 MHz S50
Reading distance of prox-keys:	1 ... 3 cm
Autonomous operation:	✓
Keyboard built-in:	✓
Communication:	Wiegand 26, Wiegand 34
Doorbell button:	✓
Tamper output:	—
Power supply:	12 V DC $\pm$ 10%
Maximal current consumption:	$\leq$ 30 mA (Standby mode) $\leq$ 60 mA (operation)
Relay contacts load:	3 A / 12 V
Main features:	• Number of relay outputs : 1, • 2000 indexed users, • Wiegand interface 26 / 34 bit • Identification: Card and/or PIN • Support for door contact and exit button • Electric strikes and electromagnetic locks support • Reversing bolt support • NO/NC output
Operation temp:	-40 °C ... 60 °C
Permissible relative humidity:	10 ... 90 % (non-condensing)

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60


"Index of Protection":	IP40
Housing:	Self-extinguishing ABS
Color:	Black + Silver
Vandal-proof:	—
Weight:	0.08 kg
Dimensions:	75 x 115 x 18 mm
Manufacturer / Brand:	ATLO
Guarantee:	3 years

PRESENTATION


Front panel view:




Mounting side view:



connector:



In the kit:



OUR OPINIONS



- No backlit keyboard.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------