

Code: KT-800

## RS-485 KEYBOARD CONTROLLER **KT-800**

Net: **286.71 EUR** Gross: **286.71 EUR**

The KT-800 control keyboard allows to remote control of dome cameras, speed dome cameras and 9CH/16CH RC series DVRs with firmware version from June 2008 or newer. The red labels buttons of the keyboard are according to the front panel DVR buttons functions. It is also possible to control many DVRs from one keyboard.  
This keyboard supports the following DVRs from our offer: RC-16600D, RC-16451H, RC-8591H.



### SPECIFICATION

Protocols:	Pelco-D, Pelco-P
Baud rates:	2.4 ... 57.6 kbps
Cameras numbers (ID):	1 ... 255
Maximal control distance:	1000 m (for 24AWG twisted-pair cable at 2400 bps)
Number of controlled devices:	255
Communication standard:	RS-485 terminals (3 Tx ports, 1 TRx port)
Manipulator:	3-axis joystick, Speed proportional to the swing (possibility of zoom control by joystick)
Display:	2 x 16 LCD
Main features:	<ul style="list-style-type: none"><li>• Programmable user preferences (presets, patterns, groups, etc.)</li><li>• Multiple protocols supported on each channel</li></ul>
Power supply:	12 V DC / 0.14 A / 9 V battery
Operation temp. / Relative humidity:	0 °C ... 40 °C / max. 70 % non-condensing
Weight:	0.7 kg
Dimensions:	280 x 174 x 92 mm
Manufacturer / Brand:	NADATEL
Guarantee:	2 years

### PRESENTATION

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: [delta-opti@delta.poznan.pl](mailto:delta-opti@delta.poznan.pl); tel: +(48) 61 864 69 60



Keyboard connectors:



In the kit:



Package:



## OUR OPINIONS



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>  
POL; 60-713 Poznań; Graniczna 10  
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

- Keyboard supports the RC series DVRs.
- User friendly and intuitive keyboard interface.
- 2-line LCD display with light time option.
- Modern and ergonomic design.



- Big sizes joystick.

#### PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

