

Code: DSTM-500

UNIVERSAL METER DSTM-500Net: **499.13 EUR** Gross: **499.13 EUR**

The DSTM-500 allows to measure the TV signals at DVB-T, DVB-S, DVB-C installations. Readable menu will help the operation for any installer. A/V input allows to view the CCTV camera images, during initialize the CCTV system, what enables to set with precision the focal, sharpness and other exposition parameters.

**SPECIFICATION**

Output and input:	2 pcs F socket, 1 pcs A/V, 1 pcs USB / 1 pcs HDMI
Frequency range:	950 MHz ... 2150 MHz - DVB-S / DVB-S2 110 MHz ... 862 MHz - DVB-T / DVB-C
Signal level:	-65 ... -25 dBm - DVB-S / DVB-S2 -93 ... -35 dBm - DVB-T / DVB-C
LNB power supply:	13/18 V, max. 400 mA
Antenna powering:	5/12/24 V, max. 50 mA
Switching between bandwidths:	0 / 22 kHz
DiSEqC:	1.0, 1.1
Modulation:	QPSK - DVB-S QPSK / 8PSK - DVB-S2 QPSK / 16-QAM / 64-QAM / 256 - DVB-T 16, 32, 64, 128, 256 QAM - DVB-C
Symbol rate:	2 ... 45 Msps - DVB-S / DVB-S2 0.2 ... 7.2 Msps - DVB-C
Processor:	32 bit, 450 MHz
SDRAM / FLASH / EEPROM:	256 MB / 2 MB NOR, 128 MB NAND / —
Video decoder:	MPEG 2, MPEG-4, H.264
Decoder bitrate:	Up to 15 Mbit/s
Resolution:	1080p, 1080i, 720p, 576p, 576i
Video format:	PAL / NTSC / SECAM
Audio decoder:	MPEG 1.2. MP3.DD/DD+, AAC/AAC+WMA9/WMA9pro
Programming and firmware upgrade:	via USB port
Battery power supply:	<ul style="list-style-type: none"> Li-Ion battery 2000 mAh 14 V / 3 A (power adapter included)
Main features:	<ul style="list-style-type: none"> Satellite scanning function Viewing the receiving channel on the LCD Car charger included in the kit DiSEqC and 22kHz control support

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Weight:	1.49 kg
Dimensions:	205 x 140 x 40 mm
Supported languages:	English, Arabic, Czech, Danish, Finnish, French, Spanish, German, Polish, Portuguese, Slovak, Swedish, Turkish, Italian
Manufacturer / Brand:	MEZON
Guarantee:	2 years

PRESENTATION

Connectors view:



Rear view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------