

Code: TM-8500

SATELLITE METER **TM-8500**

Net: **77.22 EUR** Gross: **77.22 EUR**

The TM-8500 satellite meter allows to quick set the satellite dish signal. The TM-8500 is equipped with readable menu, which helps to operate for each installer. The device has implemented over a dozen satellite positions (satellites + transponders). The TM-8500 model allows to DVB-S2 signals measurement.



SPECIFICATION

Frequency range:	950 MHz ... 2150 MHz
Signal level:	-80 ... -20 dBm
LNB power supply:	13/18 V, max. 350 mA
Switching between bandwidths:	22 kHz
DiSEqC:	DiSEqC 1.0, 1.1, 1.2, USALS systems support
Power supply:	• Li-Ion battery • Power adapter 12 V / 1 A (power adapter included) • From car power adapter (included)
Display:	2.1 " TFT LCD - with light indication
Main features:	• DVB-S / DVB-S2 signals measurement - SD and HD quality channels • Digital meter of signal level and quality • Signal level is expressed in dBμV, and quality in % • Ability to choose between Ku / C bands • Sound signaling • DiSEqC and 22kHz control support
Weight:	0.21 kg
Dimensions:	130 x 80 x 33 mm
Guarantee:	2 years

PRESENTATION

Device connectors:

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

