

Code: 3B2-98RWM

PAL VANDALPROOF CAMERA **3B2-98RWM** 3.5 ... 8 mm

Net: **31.31 USD** Gross: **31.31 USD**

Vandal-proof camera with metal housing integrated with bracket. After remove the dome cover of the camera we can set the position of the camera module (it is adjusted on any axis), the field of view of the camera changing the zoom parameter of the vari-focal lens and change the image options using OSD menu. It is equipped with IR illuminator, which is turned on by twilight sensor when illumination conditions are low.

It has been equipped with extended OSD menu with many useful functions. The DNR (Digital Noise Reduction) function produces clear image, even at poor light conditions and high image gain parameters we will not see any image noise on the screen. WDR (SSDR) - Wide Dynamic Range function enables the correct exposure (not overexposed - not underexposed) of the image at extreme different illumination of the monitoring object.

Camera connectors (BNC and power) can be hidden inside the camera housing, what protects them against damage. Additionally, camera dome cover is protected against falling by metal cable.

Camera is according to IP55 Index of Protection norm.



SPECIFICATION

Standard:	PAL
Sensor:	1/3 " Sony CCD
Resolution:	700 TVL
Lens:	3.5 ... 8 mm
View angle:	69 ° ... 33 °
Range of IR illumination:	20 m
S/N ratio:	> 50 dB
Video output:	1 Vpp / 75 Ω
Power supply:	12 V DC / 270 mA
Main features:	• WDR - Wide Dynamic Range • NR - Noise Reduction • BLC - configurable Back Light Compensation • HLC - High Light Compensation (spot) • Motion Detection - max. 4 zones • Privacy zones - max. 8 • Mirror - Horizontal mirror image • Sharpness - sharper image outlines
Vandal-proof:	✓
Permissible relative humidity:	max. 95 %
"Index of Protection":	IP55
Housing:	Dome - Metal
Color:	White
Operation temp:	-10 °C ... 50 °C
Weight:	1.1 kg
Dimensions:	183 x 132 x 146 mm
Supported languages:	English, Chinese, French, Spanish, German, Portuguese, Russian
Guarantee:	2 years

PRESENTATION



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Camera view after remove the dome cover (the vari-focal lens and configuration joystick are visible):



Mounting side view:



OUR TESTS

Camera image at artificial illumination (about 30Lux):



Camera image at night conditions with internal built-in IR illuminator on:



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Camera image at direct strong light opposite to camera:



OUR OPINIONS



- Connectors and cables can be hidden inside camera bracket.
- Solid workmanship.



- The Dome is made by using a special plastic with very good transparency, which however, should proceed carefully as it is easily scratched.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60