

Code: STX-1

AHD, HD-CVI, HD-TVI, PAL MONITOR **STX-1** 7 "

Net: **253.23 CHF** Gross: **253.23 CHF**

Multi-functional tester of AHD, HD-CVI, HD-TVI cameras, analog cameras, Speed Dome (PTZ) cameras has implemented many additional functions, necessary during initialization of the CCTV installation system.



SPECIFICATION

Standard:	AHD max. 5 Mpx @ 20 fps , HD-CVI max. 4 Mpx @ 25 fps , HD-TVI max. 5 Mpx @ 20 fps , PAL, NTSC
Screen size:	7 "
Native resolution:	800 x 480 px
Image adjustment:	✓
Sleep function:	✓
OSD menu:	✓
Video input:	<ul style="list-style-type: none">• 1 pcs AHD / HD-CVI / HD-TVI, BNC socket• 1 pcs PAL, BNC socket• 1 pcs VGA (D-Sub 15-pin)• 1 pcs HDMI - 1080p
Video output:	<ul style="list-style-type: none">• 1 pcs Video composite (Cinch socket),• 1 pcs AHD, HD-CVI, HD-TVI - Cinch socket USB / 2 x Cinch cable included in the kit
Audio input:	—
Audio output:	—
Operation as power source:	12 V DC / 1 A
Battery power supply:	Li-Ion battery
Power supply:	<ul style="list-style-type: none">• Li-Ion battery 12.6 V, 2600 mAh• 12.6 V DC / 1 A (power adapter included)
Estimated battery operation time:	max. 17 hours
Main features:	Access to the OSD menu of the HD-TVI cameras via coaxial cable

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Operation temp:	-10 °C ... 50 °C
Permissible relative humidity:	30 % ... 90 %
Weight:	0.655 kg
Dimensions:	205 x 155 x 40 mm
Supported languages:	English, Chinese Traditional, Chinese Simplified, French, Spanish, Japanese, Korean, German, Russian, Italian
Guarantee:	2 years

PRESENTATION

Front panel:



Top view:



Rear view:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

