

Code: MS-ACTHD50

AHD, HD-CVI, HD-TVI, PAL MONITOR **MS-ACTHD50** 5 "

Net: **153.63 EUR** Gross: **153.63 EUR**



SPECIFICATION

Standard:	AHD - 1080p, HD-CVI - 1080p, HD-TVI - 1080p, PAL, NTSC
Screen size:	5 "
Native resolution:	800 x 480 px
Image adjustment:	✓
Sleep function:	—
OSD menu:	✓
Video input:	• 1 pcs - AHD / HD-CVI / HD-TVI / CVBS - PAL / NTSC, BNC socket • 1 pcs VGA (D-Sub 15-pin) • 1 pcs HDMI - 1080p
Video output:	1 pcs AHD / HD-CVI / HD-TVI / CVBS - PAL / NTSC, BNC socket
Audio input:	1 pcs Jack 3.5 mm socket
Audio output:	—
RS-485 interface:	Pelco-D / Pelco-P
Operation as power source:	12 V DC / 1 A
Battery power supply:	Li-Ion battery
Power supply:	• 2 x 18650 battery 3.7 V • 5 V DC / 1.5 A - micro USB (power adapter included)
Estimated battery operation time:	max. 11 hours
Main features:	• DC 12V / 1A power source • LAN (twisted-pair) cables testing
Operation temp:	-10 °C ... 50 °C
Permissible relative humidity:	30 % ... 90 %
Weight:	0.39 kg

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Dimensions:	173 x 114 x 36 mm
Supported languages:	English, Chinese Traditional, Chinese Simplified
Guarantee:	2 years

PRESENTATION

Front panel:



Connectors view:



Rear view:



In the kit:



The tester with accessories housed in a handy bag:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------