

Code: HC-BG590-24MHD

HUNTING CAMERA HC-BG590-24MHD

Net: **115.74 EUR** Gross: **115.74 EUR**

Very good digital hunting camera, perfect to monitoring animals eg. in the forest, and also to surveillance houses, summer cottages, stores, etc. Built-in InfraRed illuminator enables recording video data also at night. Even with IR illuminator on, the device is completely invisible to the human eye, due to use the IR LEDs with 940 nm wavelength. Due to above the illuminator is completely invisible to the human eye. Camera is triggering by PIR detector and based on its settings can take one image or a few images or records a video sequence.

Minimal power consumption ensures very long and continuous operation time on batteries, even up to 6 months.

Hunting camera is full hermetic and resistant to very different environment conditions.

Warning! The hunting camera supports only SDHC cards and FAT32 file system. Remove the batteries before inserting/removing the SD card.



SPECIFICATION

Sensor:	5 Mpx CMOS
View angle:	35 °
IR illuminator wavelength:	940 nm (invisible to the human eye)
Range of IR illumination:	30 m
Number of taking photos at once:	max. 3 still images
Built-in monitor:	2 " Parameters and options display, still images playback
Internal memory:	—
External memory:	max. 32 GB SD memory card (not included)
Still image resolution:	• 24 Mpx / 18 Mpx (Day / Night) • 16 Mpx / 12 Mpx (Day / Night) • 10 Mpx / 8 Mpx (Day / Night)
Video sequence resolution:	1920 x 1080 @ 20 fps 1280 x 720 @ 20 fps 640 x 480 @ 20 fps
Video sequence duration time:	5 ... 180 s
Day/night mode:	ICR automatic filter
PIR detection range:	30 m
PIR detector:	with adjustable sensitivity (3 levels)
Detection angle:	55 °

DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

Battery power supply:	• 4 / 8 pcs LR6 (AA) • DC 6V/12W power adapter (not included)
Stand-by power consumption:	< 300 μ A - Battery supply is sufficient for approx. 6 months of operation in Standby mode
Operating power consumption:	< 150 mA (350mA with IR illuminator on) In still images capture mode, battery supply is sufficient for approx. 3000 images
Operation temp:	-20 °C ... 60 °C
Permissible relative humidity:	5 ... 90 % (non-condensing)
Main features:	Time Lapse function - takes a picture at a specified time, regardless of whether there is motion (5, 10, 15min ... 55min, 1h ... 8h)
Weight:	0.31 kg
Dimensions:	102 x 157 x 74 mm
Supported languages:	English, French, Spanish
Guarantee:	2 years

PRESENTATION

Front view:



Internal view (after open the enclosure):



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
 POL; 60-713 Poznań; Graniczna 10
 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



Connectors view:



Bottom view:



Mounting side view:



In the kit:



OUR TESTS



OUR OPINIONS



- Very long operation time with battery supply.

PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------



DELTA-OPTI Monika Matysiak; <https://www.delta.poznan.pl>
POL; 60-713 Poznań; Graniczna 10
e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60