

NVR TC-R3105 SPEC:I/B/L/EU/V1.1 5 CHANNELS TIANDYNet: **71.52 GBP** Gross: **71.52 GBP**

The product has been designed to minimize costs while maintaining high quality and ease of use.

**SPECIFICATION**

Standard:	IP
Supported resolutions:	max. 6 Mpx
Video outputs:	1 pcs HDMI 4K 1 pcs VGA
Audio support:	5 Channels - Audio from cameras
Audio inputs:	—
Audio outputs:	—
Image compression method:	S+265 / H.265 / H.264
Supported hard drives:	1 x 8 TB SATA
Recording modes:	Manual, Motion Detection, Schedule
External storage devices backup:	Backup to USB drive (pendrive, external drive)
Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) 1/4 channel synchronous playback
Network interface:	1 x RJ-45 - 10 / 100 Mbps
Network functions:	Full support via network, Remote records copying, Web-Server built-in
ONVIF:	✓
Bitrate:	max. 60 Mbps
Default admin user / password:	admin / - The administrator password should be set at the first start
Default IP address:	192.168.1.3
RTSP URL:	rtsp://user:password@192.168.1.3:554/1/1 - Main stream rtsp://user:password@192.168.1.3:554/1/2 - Sub stream
Web browser access ports:	80, 443, 3000, 3001, 3002, 23002
PC client access ports:	3000, 3001

Mobile client access ports:	3000, 3001
Mobile phones support:	Port no.: 3000 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application EasyLive Plus • iOS (iPhone): Free application EasyLive Plus
Access from PC:	Port no.: 3000 or access by a cloud (P2P) - PC: Free application Easy7 Smart Client Express
Alarm inputs / outputs:	—
PTZ control:	✓
Motion Detection:	✓
Intelligent image analysis:	—
USB:	2 x USB 2.0
Mouse support:	✓
IR remote controller in the set:	—
Main features:	Support for Intelligent Image Analysis function, available in TIANDY cameras : <ul style="list-style-type: none"> • crossing the line (tripwire) • double crossing the line • abandoned/missing object • detection of loitering in a given area • running • parking detection • detection of people gathering • protective helmet detection • detection of persons on duty • signal loss indication
Power supply:	12 V DC / 1.5 A (power adapter included)
Weight:	0.42 kg
Dimensions:	201 x 201 x 43 mm
Supported languages:	English, Russian
Manufacturer / Brand:	TIANDY
Guarantee:	3 years

PRESENTATION

Top view:



Rear panel:



In the kit:



PACKAGE

Dimensions (L x W x H): 0x0x0 mm	Gross Weight: 0 kg
----------------------------------	--------------------

